

4214

MULTIPLIER - DIVIDER

FEATURES

- DIFFERENTIAL INPUTS
- LASER-TRIMMED
- GUARANTEED ACCURACY
0.5% and 1%
- SELF-CONTAINED
No additional parts required
- LOW NOISE
120Vrms, 10Hz - 10kHz
- DIP PACKAGE

DESCRIPTION

The 4214 family of multipliers are low-cost integrated circuit multiplier/dividers designed for general purpose usage. In addition to four-quadrant multiplication, they also perform division and square rooting of analog signals. They do not require use of additional amplifiers to perform these functions. The 4214 is laser-trimmed prior to final packaging and is guaranteed to its rated accuracy with no external components—a distinct advantage from standpoints of cost and reliability.

APPLICATIONS

- MULTIPLICATION
- DIVISION
- SQUARING
- SQUARE ROOTING
- ADAPTIVE CONTROL
- ALGEBRAIC COMPUTATION
- POWER COMPUTATION

The 4214 contains its own zener-regulated references and, as a result, is much less sensitive to supply voltage variation than were earlier IC multipliers. The multipliers' output noise is only 120Vrms in a 10Hz to 10kHz bandwidth.

The unit is packaged in a 14-pin ceramic DIP package and available in both -25°C to $+85^{\circ}\text{C}$ and -55°C to $+125^{\circ}\text{C}$ specification temperature ranges.

SPECIFICATIONS

ELECTRICAL

Typical performance at +25°C with rated power supplies unless otherwise noted.

MODEL	4214AP/RM	4214BP/SM
OUTPUT FUNCTION	$\frac{(X_1 - X_2)(Y_1 - Y_2)}{10} + Z_2$	
TOTAL ERROR⁽¹⁾ Without Trimming Error vs Temperature (-25°C to +85°C), (AP and BP) (-55°C to +125°C), (RM and SM) Error vs Supply	1% max 0.008%/°C typ., 0.02%/°C max 0.025%/°C typ., 0.05%/°C max	0.5% max 0.02%/°C max 0.05%/°C max
INDIVIDUAL ERRORS Output Offset vs Temperature vs Supply Scale Factor Error vs Temperature vs Supply Nonlinearity X (X = 20V p-p, Y = ±10VDC) Y (Y = 20V p-p, X = ±10VDC) Feedthrough at 50 Hz X = 20V p-p, Y = 0 Y = 20V p-p, X = 0 vs Temperature vs Supply	10mV typ 50mV max 0.7mV/°C typ 2mV/°C max	7mV typ 25mV max 0.3mV/°C typ 0.7mV/°C max 0.25mV/% 0.12% 0.008%/°C 0.05%/°C ±0.08% ±0.01% 30mV p-p 6mV p-p 0.1mV p-p/°C 0.15mV p-p/%
AC PERFORMANCE Small Signal ±3dB Flatness Small Signal ±1% Flatness Small Signal ±1% Vector Error (0.57° Phase Shift) Full Power Bandwidth Slew Rate Settling Time to 1% (20V step)		610 kHz 90 kHz 7.5 kHz 330 kHz 23V/μs 1.7μs
OUTPUT NOISE (X = Y = 0) 10 Hz to 10 kHz 10 Hz to 10 MHz		120μV rms 700μV rms
INPUT CHARACTERISTICS Input Voltage Range Rated Operation, min. Absolute max Input Impedance, X, Y, Z ² Input Bias Current, X, Y, Z		±10V ±V _s 10 MΩ 1.4μA
OUTPUT CHARACTERISTICS Rated Output Output Impedance		±10V at ±5mA min 1.5Ω
POWER SUPPLY REQUIREMENTS Rated Voltage Operating Range Quiescent Current		±15V ±8.5VDC to ±20VDC ±5.5mA
TEMPERATURE RANGE Rated Performance (specification) Operation Storage	AP and BP RM and SM	-25°C to +85°C -55°C to +125°C -55°C to +125°C -65°C to +150°C

- Total error is the maximum allowed value of the sum of the individual errors.
- Z₂ input impedance is 10 MΩ typ with Pin 11 open circuit. If Pin 11 is grounded or used for optional offset adjustment the Z₂ input impedance may become as low as 25kΩ.

MECHANICAL

Ceramic Dual-in-Line

NOTE: Leads in true position within 0.010" (0.25mm) R at MMC at seating plane.

Pin numbers shown for reference only. Numbers may not be marked on package.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.670	.710	17.02	18.03
C	.066	.170	1.65	4.32
D	.015	.021	0.38	0.53
F	.045	.090	1.14	1.52
G	100 BASIC		2.54 BASIC	
H	.025	.070	0.64	1.78
J	.008	.012	0.20	0.30
⌀	.120	.240	3.05	6.10
L	300 BASIC		7.62 BASIC	
M	— 10°		— 10°	
N	.009	.090	0.23	1.52

CONNECTION DIAGRAM

TYPICAL PERFORMANCE CURVES





FIGURE 4. Input Range for Linear Response.




FIGURE 5. Nonlinearity vs. Frequency.




FIGURE 3. Small-signal Frequency Response.




FIGURE 6. Feedthrough vs. Frequency.




FIGURE 7. Max. Output Voltage vs. Output Current.





FIGURE 10. Simplified Equivalent Circuit.

OPERATING MODES MULTIPLICATION

The 4214 is a general purpose multiplier/divider with three sets of differential inputs viz. X, Y, and Z. Its open-loop transfer function is

$$e_o = A \left[\frac{(X_1 - X_2)(Y_1 - Y_2)}{10} - (Z_1 - Z_2) \right]$$

where, A is the open-loop gain of the internal output amplifier (see the simplified equivalent circuit, Figure 10). Due to very high gain ($A \rightarrow \infty$) of the output amplifier the feedback from the output to any of the inputs will establish the relationship

$$Z_1 - Z_2 = (X_1 - X_2)(Y_1 - Y_2) / 10$$

Taking output at Z_1 the multiplication mode transfer function is obtained and is expressed as

$$e_o = \frac{(X_1 - X_2)(Y_1 - Y_2)}{10} + Z_2$$

This connection of 4214 is shown on page 2.

DIVISION

The 4214 may be used as a two quadrant divider, without the need for an external op amp. Note that the maximum output error in the divide mode is given approximately by,

$$\text{Divider error} \approx \frac{10 \epsilon_m}{X_1 - X_2}, \text{ where } \epsilon_m \text{ is}$$

the total error specified for the multiply mode. The divider error, as shown above, becomes excessively large for small values of $(X_1 - X_2)$. A 10:1 denominator range is usually the practical limit. This is true for all such units, where a multiplier is used in voltage feedback mode to generate "divide" function.

If more accurate division is required over wide range of denominator voltages, the Burr-Brown model 4291 is recommended (0.25% max error over 100:1 range).

For optimum performance, the Z offset should be nulled by letting the input be zero and adjusting R_1 for zero output. This offset adjustment will improve the divider error to about $\frac{3 \epsilon_m}{(X_1 - X_2)}$ for $(X_1 - X_2)$ much less than 10V.

FIGURE 11. Divide Mode Connections—4214.

SQUARE ROOT

By applying feedback from the output to both the X and Y inputs, the square root function can be obtained. The errors in the square root mode become large for small values of Z input. The actual output is approximately

$$\text{Square root output } e_o = \sqrt{10(Z_1 - Z_2) + 10 \epsilon_m}$$

where ϵ_m is the total error for the multiply mode.

Burr-Brown's multifunction converter model 4302 is recommended for applications requiring more accuracy over wider dynamic range.

The output offset should be nulled for optimum performance by allowing the input to be its smallest expected value and adjusting R_1 for the proper output voltage.




FIGURE 12. Square Root Mode Connections—4214.

SINE FUNCTION GENERATOR

Two 4214's can be connected with implicit feedback as shown in Figure 13 to implement the following sine function approximation.

$$e_o = \frac{1.5715 e_i - 0.004317 e_i^3}{1 + 0.001398 e_i^2} = 10 \text{ Sin } 9 e_i$$

The theory and procedures for developing virtually any function generator or linearization circuit can be found in the new Burr-Brown/McGraw Hill book "FUNCTION CIRCUIT - Design and Applications."




FIGURE 13. Sine Function Connections—4214.

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/Ball Finish	MSL Peak Temp ⁽³⁾
4214AP	NRND	CDIP SB	JD	14		TBD	Call TI	Call TI

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
RF/IF and ZigBee® Solutions	www.ti.com/lprf

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Medical	www.ti.com/medical
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2009, Texas Instruments Incorporated