



MATERIAL: COPPER  
 .031" NOM. THICKNESS  
 FINISH: ELECTRO-TIN PLATING

MWID= MAX. WIRE INSULATION DIA.  
 PART NUMBERS ARE FOR LOOSE PIECE TO ORDER PARTS ON TAPE ADD A "T" TO END OF PART NUMBER

MATERIAL NO.	ENGR NO.	WIRE RANGE AWG	DIAMETER "D"	MAX. "L"	±.01 "B"	MWID	MIN. I.D.			INSULATION
190340002	A-259X	22-18	.180	.950	.450	.145	.056			PVC
190340005	A-269X	22-18	.156	.890	.450	.145	.056			PVC
190340007	B-279X	16-14	.180	.950	.450	.175	.084			PVC
190340009	B-289X	16-14	.156	.890	.450	.175	.084			PVC

REMOVED TAPE PARTS

EC NO:	2005/04/27
DRWN:LSHADECK	2005/05/04
CHKDR:DEROSS	2005/05/04
APPR:RDEROSS	2005/05/04

QUALITY SYMBOLS	DESCRIPTION
▽=0	
▽=0	

GENERAL TOLERANCES (UNLESS SPECIFIED)	
	mm INCH
4 PLACES	± --- ± ---
3 PLACES	± --- ± ---
2 PLACES	± --- ± ---
1 PLACE	± --- ± ---
ANGULAR	± ---°
DRAFT WHERE APPLICABLE	MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	IN/MM
SCALE	5:1
DESIGN UNITS	INCH
THIRD ANGLE PROJECTION	
DRAWN BY	DATE
EMF	07/30/93
CHECKED BY	DATE
JM	07/30/93
APPROVED BY	DATE
FP	07/30/93

TITLE	INSULKRIMP MALE BULLET SNAP PLUG
MATERIAL NO.	SEE TABLE
DOCUMENT NO.	SD-19034-004
SHEET NO.	1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	