
# EVC009

## Connecting cable with socket

ADOAH043MSS0010H04

Please see the technical note under "Downloads"




| | | |
|---|---|---|
| **Application** | | |
| Special feature | | Free from silicone; Halogen-free; Gold-plated contacts; Drag chain suitability |
| Free from silicone | | yes |
| **Electrical data** | | |
| Operating voltage | [V] | 10...36 DC |
| Protection class | | II |
| Max. current load total | [A] | 4 |
| **Outputs** | | |
| Electrical design | | PNP |
| **Operating conditions** | | |
| Ambient temperature | [°C] | -25...90 |
| Note on ambient temperature | | cULus: ...75 |
| Ambient temperature (moving) | [°C] | -25...90 |
| Note on ambient temperature (moving) | | cULus: ...75 |
| Protection | | IP 65; IP 67; IP 68; IP 69K |
| **Tests / approvals** | | |
| MTTF | [years] | 20027 |

# EVC009

## Connecting cable with socket

ADOAH043MSS0010H04


| Mechanical data | | | |
|---|---|---|---|
| Weight | [g] | 286.4 | |
| Dimensions | [mm] | 26.5 x 15.5 x 36.5 | |
| Materials | | housing: TPU black transparent; Sealing: FKM | |
| Material nut | | brass, nickel-plated | |
| Drag chain suitability | | yes | |
| Drag chain suitability | | bending radius for flexible use | min. 10 x cable diameter |
| | | travel speed | max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s² |
| | | bending cycles | > 5 Mio. |
| | | torsional strain | ± 180 °/m |
| **Displays / operating elements** | | | |
| Display | | switching status | 2 x LED, yellow |
| | | operation | 1 x LED, green |
| **Remarks** | | | |
| Notes | | Please see the technical note under "Downloads" | |
| Pack quantity | | 1 pcs. | |

**Electrical connection**

Cable: 10 m, PUR, Halogen-free, black, Ø 4.3 mm; 4 x 0.34 mm² (42 x Ø 0.1 mm )

**Electrical connection - socket**

Connector: 1 x M12, angled; coding: A; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.6...1.5 Nm




# EVC009

## Connecting cable with socket

**ADOAH043MSS0010H04**

### Connection




| | |
|---|---|
| | Core colours : |
| BK = | black |
| BN = | brown |
| BU = | blue |
| WH = | white |