PART NO.	A79102-001	REV	ECO	DATE	APP
		D	98556	05-17-12	TLM

MATERIALS & SPECIFICATIONS

INSULATOR MATERIAL:
THERMOPLASTIC POLYMER PER MIL-DTL-32139

CONTACT MATERIAL:
COPPER ALLOY PER MIL-DTL-32139. GOLD PLATED PER ASTM B488, (HARD GOLD) TYPE II CODE C CLASS 1.27


TERMINATION:
32 AWG (7-40) TYPE ET, PER NEMA HP3, COLOR CODED PER TABLE

CURRENT CAPACITY:
1 AMP MAX PER MIL-DTL-32139

CONTACT RESISTANCE:
71 MILLIOHMS (71 mV) MAX @ 1.0 AMPS PER MIL-DTL-32139



ACTUAL SIZE
EXCLUDING WIRE LENGTH



SECTION A-A

LOADING VIEW
LESS EPOXY

PIN #	COLOR
1, 11	BLACK
2	BROWN
3	RED
4	ORANGE
5	YELLOW
6	GREEN
7	BLUE
8	VIOLET
9	GRAY
10	WHITE

INTERNAL USE ONLY

USE MFG. LOADING
PROCEDURE NC-11P

RoHS

NCP
SLDW

THIRD ANGLE

-TOLERANCES-
UNLESS OTHERWISE NOTED
DIMENSIONS IN INCHES
2 PL DEC ± .01
3 PL DEC ± .005
4 PL DEC ± .0005
ANGLES ± 1°

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP.

		DATE
DFTM. TLM		01-14-09
CHK'D.		DATE
APP'D.		DATE

TITLE:
(11) PIN MALE
NANO CIRCULAR
CONNECTOR

OMNETICS
CONNECTOR CORPORATION
7260 COMMERCE CIRCLE EAST
MINNEAPOLIS, MN 55432
WWW.OMNETICS.COM

CAGE CODE 61873
DWG NO.
A79102-001
SHEET 1 OF 1
REV D
SCALE: 4:1