


REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1	-	TECHNICAL DATA SHEET RELEASE	12-MAY-14	KMM	RFC





WIRING DIAGRAM



TECHNICAL DATA:

1) MATERIALS:
   - HOUSING: MACHINED ALUMINUM, ANODIZED
   - INSULATION INSERT: THERMOPLASTIC, UL 94/V-0
   - CONTACT: GOLD FLASH PLATING OVER COPPER ALLOY
   - CONDUCTOR INSULATION: PVC
   - NUMBER OF CONDUCTORS: (4) 10AWG

2) ELECTRICAL DATA:
   - CURRENT (MAX): 25A
   - VOLTAGE (MAX): 600V AC/DC
   - INSULATION RESISTANCE (MIN): 5000M OHMS
   - DIELECTRIC TEST VOLTAGE: 2200V

3) MECHANICAL DATA:
   - KNOCKOUT HOLE SIZE FOR PANEL MOUNT: 22.2mm [.88"]
   - TEMPERATURE RANGE: -40°C TO 90°C
   - PROTECTION: IP67 (MATED CONDITION)
   - MATING CYCLES: >500
   - VIBRATION RESISTANCE PER MIL-STD-202 METHOD 204
   - THERMAL SHOCK PER MIL-STD-202 METHOD 207
   - 48 HOUR SALT SPRAY PER MIL-STD-202 METHOD 101

4) RoHS COMPLIANT

5) UL 2237 LISTED ASSEMBLY
   UL FILE NUMBERS: E339703

TOLERANCE	
0-2.99 M = +100.0/-25.0mm	0-9.99 FT = +4" / -1"
3-8.99 M = +150.0/-25.0mm	10.00-29.99 FT = +6" / -1"
9-14.99 M = +300.0/-25.0mm	30.00-49.99 FT = +12" / -1"
15-OVER M = +450.0/-25.0mm	50 FT-OVER = +18" / -1"

Risk of Electrical Shock
Do Not Disconnect Under Load.
Risque de chocs electriques
Ne pas debrancher sous tension.
⚠WARNING

	PART NUMBER	DESCRIPTION	ITEM
QUANTITY	MATERIALS LIST		

UNLESS OTHERWISE SPECIFIED
1) All dimensions are in metric(mm).
2) Tolerances are as follows:
1 PL DEC ±0.30 | Fractions ±1/64
2 PL DEC ±0.15 | Angles ±1°
3 PL DEC ±0.08
3) Note reference = X

MATERIAL SPECIFICATIONS:

PROCESS SPECIFICATIONS:

NEXT ASS'Y:

SIGNATURES		DATE
DRAWN:	KMM	12-MAY-14
CHECKED:	MRF	12-MAY-14
ENGINEER:	KMM	
APPROVAL:	RFC	12-MAY-14
CUSTOMER:		

THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.

Amphenol

Sine Systems - www.amphenol-sine.com
44724 Morley Drive
Clinton Township, MI 48036

M35 PB LITE, 4 PIN, FEMALE RECEPTACLE
TRUNK, 10 AWG, 1/2 - 14NPT

SIZE	TYPE	DWG NO:	REVISION
	C-	P29026-Mxxx	A1

SCALE: FULL | C-P29026 | SHEET 1 OF 1

TITLE: M35 PB LITE, 4 PIN, FEMALE REC., 10AWG, 1/2-14NPT
DWG NO: C-P29026-Mxxx
REV: A1
SH: 1
OF: 1