# Flush-type connector - SACC-E-MS-8CON-M16/0,5 SCO - 1523492

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Sensor/Actuator flush-type plug, 8-pos., M12-SPEEDCON, A-coded, front/screw mounting with M16 thread, with 0.5 m TPE litz wire, 8 x 0.25 mm²

## Key commercial data

| | |
|---|---|
| Packing unit | 1 |
| Minimum order quantity | 1 |
| Catalog page | Page 28 (PC-2011) |
| GTIN | 4 046356 021326 |
| Custom tariff number | 85444290 |
| Country of origin | GERMANY |

## Technical data

### General data

| | |
|---|---|
| Rated current at 40°C | 2 A |
| Rated voltage | 30 V |
| Number of positions | 8 |
| Volume resistance | ≤ 3 mΩ |
| Insulation resistance | ≥ 100 MΩ |
| Length of cable | 0.5 m |
| Ambient temperature (operation) | -25 °C ... 85 °C (Male connector / female connector) |

### General characteristics

| | |
|---|---|
| Standards/regulations | M12 plug-in connector IEC 61076-2-101 |
| Coding | A - standard |
| Surge voltage category | II |
| Pollution degree | 3 |
| Degree of protection | IP67 |
| Contact material | CuZn |
| Contact surface material | Ni/Au |
| Contact carrier material | PA 66 |
| Material, knurls | Zinc die-cast, nickel-plated |

# Flush-type connector - SACC-E-MS-8CON-M16/0,5 SCO - 1523492

## Technical data

### General characteristics

| | |
|---|---|
| Sealing material | NBR |
| Mounting type | Front mounting M16 x 1.5 |
| Connection method | Individual wires |
| Status display | No |

### Conductor data

| | |
|---|---|
| Cable type | TPE litz wire |
| Conductor cross section | 0.25 mm² |
| AWG signal line | 24 |
| Conductor structure signal line | 14x 0.15 mm |
| Core diameter including insulation | 1.15 mm ±0.07 mm |
| Thickness, insulation | 0.21 mm (Core insulation) |
| Wire colors | Brown, blue, white, gray, pink, green, yellow, red |
| Material conductor insulation | TPE |
| Conductor material | Tin-plated Cu litz wires |
| Insulation resistance | ≥ 20 MΩ*km |
| Conductor resistance | ≤ 80 mΩ/m |
| Nominal voltage, conductor | 300 V |
| Test voltage, conductor | 2000 V AC |
| Ambient temperature (operation) | -25 °C ... 90 °C (cable, fixed installation) |

## Classifications

### eclass

| | |
|---|---|
| eCl@ss 4.0 | 27140815 |
| eCl@ss 4.1 | 27140815 |
| eCl@ss 5.0 | 27143423 |
| eCl@ss 5.1 | 27143423 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 7.0 | 27449001 |

### etim

| | |
|---|---|
| ETIM 2.0 | EC001297 |
| ETIM 3.0 | EC002061 |
| ETIM 4.0 | EC002061 |

### unspsc

| | |
|---|---|
| UNSPSC 6.01 | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11 | 31251501 |
| UNSPSC 12.01 | 31251501 |
| UNSPSC 13.2 | 31251501 |

# Flush-type connector - SACC-E-MS-8CON-M16/0,5 SCO - 1523492

## Approvals

### Approvals

Approvals

UL Recognized

Ex Approvals

Approvals submitted


### Approval details

UL Recognized

| | |
|---|---|
| mm²/AWG/kcmil | 26-2 |
| Nominal current IN | 2 A |
| Nominal voltage UN | 30 V |


## Drawings

Dimensioned drawing




Housing cutout for M16 fastening thread, mounting panel with thread


Dimensioned drawing




Housing cutout for M16 fastening thread, mounting panel with feed-through hole (alternatively with surface as protection against rotation)


# Flush-type connector - SACC-E-MS-8CON-M16/0,5 SCO - 1523492

Schematic diagram





Pin assignment M12 plug, 8-pos., view plug side

Dimensioned drawing




M12 flush-type connector

Circuit diagram




Contact assignment of the M12 plug

© Phoenix Contact 2012 - all rights reserved
http://www.phoenixcontact.com