3M™ TWIN AXIAL PCI EXPRESS X8 EXTENDER ASSEMBLIES GEN 4.0, 8KH9 SERIES


BILL OF MATERIALS			
	ITEM	DESCRIPTION	QTY
1.0	PBA	PCB ASSY, PADDLECARD, PCIE X8	1
1.1	PCB	PCIE X8 (98 POS) SURFACEMOUNT 3M P/N: 78-9102-8020-1	1
1.2	CONN	CONNECTOR, PCIE (98 POS) SMT. X8 GEN 5	1
2.0	PCB	PCIE X8 EXTENDER (98 POS) CARD-EDGE 3M P/N: 78-9102-8014-4	1
3.0	CABLE	RIBBON TWINAX CABLE 3M P/N: SL8802/22-15FN5-00	AS REQUIRED
4.0	CABLE	RIBBON CABLE, 20 POSITION 3M P/N: HF447-20	AS REQUIRED
5.0	STRAIN RELIEF	ADHESIVE	AS REQUIRED
6.0	LABEL	SEE ASSEMBLY PART DETAIL	1


ORDERING INFORMATION


8KH9-0968-XXXX

STANDARD LENGTHS DIM. "A"
0250 = [250 MM]
0500 = [500 MM]

NOTE:
NON-STANDARD LENGTHS AVAILABLE UPON REQUEST.
MAY REQUIRE HIGHER MOQ'S AND LONGER LEAD TIMES.







NOTES

1. DIMENSIONS ARE IN MILLIMETERS.
2. 3M TWIN AXIAL CABLE DESCRIPTION:
   30 AWG, SILVER PLATED SIGNAL WIRE
   IMPEDANCE: 85 ±5 OHM
   OVERALL RIBBON WIDTH: 24.90 MM
   OVERALL RIBBON THICKNESS: 0.75 MM
3. REGULATORY INFORMATION:
   VISIT 3M.com/regs OR CONTACT YOUR 3M REPRESENTATIVE TO FIND THE RoHS COMPLIANCE STATUS OF THE 3M PART YOU ARE INTERESTED IN.
6. THIS CABLE CONSTRUCTION HAS A THIN ALUMINUM LAYER AT EACH EDGE. USER SHOULD EVALUATE ITS USE IN THEIR APPLICATION AND, IF NECESSARY, INSULATING TAPE MAY BE APPLIED TO COVER THE ALUMINUM LAYER, AS USER DEEMS APPROPRIATE.
7. PRODUCT SPECIFICATION: PS-0390.
8. FLAMMABILITY RATING
   -TWINAX/AUX RIBBONS: UL94 HB HORIZONTAL FLAME TEST FOR INTERNAL WIRING
   -PCBS: UL94V-0
9. PADDLECARD PLATING:
   30μ" MIN. GOLD PLATING
   50μ" MIN. NICKEL UNDERPLATING.
10. UNLESS OTHERWISE NOTED, REFERENCES TO INDUSTRY SPECIFICATIONS ARE INTENDED TO INDICATE SUBSTANTIAL COMPLIANCE TO THE MATERIAL ELEMENTS OF THE SPECIFICATION. SUCH REFERENCES SHOULD NOT BE CONSTRUED AS A GUARANTEE OF COMPLIANCE TO ALL REQUIREMENTS IN A GIVEN SPECIFICATION.
11. CLOTH TAPE WRAPPED AROUND CABLE RIBBONS AT BACK OF EACH CONNECTOR. ALSO, UP TO TWO ADDITIONAL TAPE PIECES WILL BE WRAPPED AROUND THE TWO CABLE RIBBONS SPACED EQUIDISTANT FROM THE CONNECTOR ENDS AND EACH OTHER, DEPENDING ONASS'Y LENGTH (L):
    L <=0.2M: NO ADDITIONAL TAPE
    0.2M < L <= 0.6M: 1 TAPE WRAP
    0.6M < L <= 1.0M: 2 TAPE WRAP
12. LENGTH TOLERANCE:
    ±5MM FOR LENGTHS LESS THAN 0.5M.
    ±8MM FOR LENGTHS 0.5 TO 1.0 METER.
13. (X) DENOTES ITEM FIND NUMBER IN TABLE 1: BILL OF MATERIALS.
14. (C) DENOTES CRITICAL DIMENSION.

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
http://www.3m.com/TwinAx

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING INFORMATION CALL 800-225-5373

REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
A	0106397	AUG 15,2022 WORK REQUEST 13204 PRODUCTION RELEASE	LDS	MML

DESIGN REFERENCE | NEXT ASSEMBLY | ACCESS CODES

DRFT CASTIGLIONE — DATE MAR 15,2019 — MFG — DATE
CHKD M LETTANG — DATE AUG 15,2022 — APPVL — DATE

DIVISION | DIVISION CODE EMSD

DO NOT SCALE DRAWING | SCALE 2/1

TOLERANCES EXCEPT AS NOTED
INCHES .0 ± / .00 ± / .000 ± / .0000 ±
MILLIMETERS 0 ±1 / .0 ±.5 / .00 ±.05 / .000 ±.005
ANGLES ±

THIRD ANGLE PROJECTION
INTERPRET PER ASME Y14.5 - 2018
MAX SURFACE ROUGHNESS ☐ ALL SURFACES ☐ MARKED ONLY

3M Center St. Paul, MN 55144
© 3M COPYRIGHT 2022
This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.

TITLE: 8KH9-0968-XXXX CABLE ASSY, X8 GEN 4.0 SMT EXTENDER, PCIE

CAGE NUMBER | SIZE D | DRAWING NO. 78-5100-2687-1 | REV. A

MODEL | DET LISTS ☐ YES ☒ NO | SHT 1 OF 2

78-5100-2687-1 A

Imaged: Central Standard Time 8/15/2022 -- UTC Offset (hrs) 6

3M™ TWIN AXIAL PCI EXPRESS X8 EXTENDER ASSEMBLIES GEN 4.0, 8KH9 SERIES

Edgecard pin #	Side B Description	Name	CEM pin #
B01	+12 volt power	+12v	B01
B02	+12 volt power	+12v	B02
B03	+12 volt power	+12v	B03
B04	Ground	GND	B04
B05	SMBus clock	SMCLK	B05
B06	SMBus data	SMDAT	B06
B07	Ground	GND	B07
B08	+3.3 volt power	+3.3v	B08
B09	+TRST#	JTAG1	B09
B10	3.3v auxiliary power	3.3Vaux	B10
B11	Link Reactivation	WAKE#	B11
	Mechanical Key		
B12	Clock Request Signal	CLKREQ#	B12
B13	Ground	GND	B13
B14	Transmitter Lane 0, Differential pair	PETp(0)	B14
B15		PETn(0)	B15
B16	Ground	GND	B16
B17	Presence detect	PRSNT2#	B17
B18	Ground	GND	B18
B19	Transmitter Lane 1, Differential pair	PETp(1)	B19
B20		PETn(1)	B20
B21	Ground	GND	B21
B22	Ground	GND	B22
B23	Transmitter Lane 2, Differential pair	PETp(2)	B23
B24		PETn(2)	B24
B25	Ground	GND	B25
B26	Ground	GND	B26
B27	Transmitter Lane 3, Differential pair	PETp(3)	B27
B28		PETn(3)	B28
B29	Ground	GND	B29
B30	Emergency Pwr Reduct	PWRBRK#	B30
B31	Presence detect	PRSNT2#	B31
B32	Ground	GND	B32
B33	Transmitter Lane 4, Differential pair	PETp(4)	B33
B34		PETn(4)	B34
B35	Ground	GND	B35
B36	Ground	GND	B36
B37	Transmitter Lane 5, Differential pair	PETp(5)	B37
B38		PETn(5)	B38
B39	Ground	GND	B39
B40	Ground	GND	B40
B41	Transmitter Lane 6, Differential pair	PETp(6)	B41
B42		PETn(6)	B42
B43	Ground	GND	B43
B44	Ground	GND	B44
B45	Transmitter Lane 7, Differential pair	PETp(7)	B45
B46		PETn(7)	B46
B47	Ground	GND	B47
B48	Presence detect	PRSNT2#	B48
B49	Ground	GND	B49

Edgecard pin #	Side A Description	Name	CEM pin #
A01	Presence detect	PRSNT#1	A01
A02	+12 volt power	+12v	A02
A03	+12 volt power	+12v	A03
A04	Ground	GND	A04
A05	TCK	JTAG2	A05
A06	TDI	JTAG3	A06
A07	TDO	JTAG4	A07
A08	TMS	JTAG5	A08
A09	+3.3 volt power	+3.3v	A09
A10	+3.3 volt power	+3.3v	A10
A11	Fundamental reset	PERST#	A11
	Mechanical Key		
A12	Ground	GND	A12
A13	Reference Clock, Differential pair	REFCLK+	A13
A14		REFCLK-	A14
A15	Ground	GND	A15
A16	Receiver Lane 0, Differential pair	PERp(0)	A16
A17		PERn(0)	A17
A18	Ground	GND	A18
A19	Manufacturer Test Mode	MFG	A19
A20	Ground	GND	A20
A21	Receiver Lane 1, Differential pair	PERp(1)	A21
A22		PERn(1)	A22
A23	Ground	GND	A23
A24	Ground	GND	A24
A25	Receiver Lane 2, Differential pair	PERp(2)	A25
A26		PERn(2)	A26
A27	Ground	GND	A27
A28	Ground	GND	A28
A29	Receiver Lane 3, Differential pair	PERp(3)	A29
A30		PERn(3)	A30
A31	Ground	GND	A31
A32	Reserved	RSVD	A32
A33	Reserved	RSVD	A33
A34	Ground	GND	A34
A35	Receiver Lane 4, Differential pair	PERp(4)	A35
A36		PERn(4)	A36
A37	Ground	GND	A37
A38	Ground	GND	A38
A39	Receiver Lane 5, Differential pair	PERp(5)	A39
A40		PERn(5)	A40
A41	Ground	GND	A41
A42	Ground	GND	A42
A43	Receiver Lane 6, Differential pair	PERp(6)	A43
A44		PERn(6)	A44
A45	Ground	GND	A45
A46	Ground	GND	A46
A47	Receiver Lane 7, Differential pair	PERp(7)	A47
A48		PERn(7)	A48
A49	Ground	GND	A49

ALL GROUNDS ARE TIED TOGETHER IN PCBS

Regulatory: For regulatory information about this product, visit 3M.com/regs or contact your 3M representative.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OR TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M Company
Electronics Materials Solutions Division
13011 McCallen Pass, Bldg. C
Austin, TX 78753-5380
1-800-225-5373
www.3M.com/interconnect

REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
A	0106397	AUG 15,2022 WORK REQUEST 13204 PRODUCTION RELEASE	LDS	MML

DESIGN REFERENCE / NEXT ASSEMBLY
ACCESS CODES
DRFT: CASTIGLIONE — DATE: MAR 15,2019 — MFG — DATE
CHKD: M LETTANG — DATE: AUG 15,2022 — APPVL — DATE
DIVISION
DIVISION CODE: EMSD
DO NOT SCALE DRAWING — SCALE 1/1
TOLERANCES EXCEPT AS NOTED
INCHES: .0 X, .00 ±, .000 ±, .0000 ±
THIRD ANGLE PROJECTION
INTERPRET PER ASME Y14.5 - 2018
MILLIMETERS: 0 ±1, .0 ±.5, .00 ±.05, .000 ±.005
MAX SURFACE ROUGHNESS: ALL SURFACES / MARKED ONLY
ANGLES ±1

3M Center, St. Paul, MN 55144

© 3M COPYRIGHT 2022
This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.

TITLE: 8KH9-0968-XXXX CABLE ASSY, X8 GEN 4.0 SMT EXTENDER, PCIE

CAGE NUMBER | SIZE: D | DRAWING NO.: 78-5100-2687-1 | REV.: A
MODEL
DET. LISTS ☐ YES ☒ NO | SHT 2 OF 2

78-5100-2687-1 DATA NO LABOR | A REVISION

Imaged: Central Standard Time 8/15/2022 -- UTC Offset (hrs) 6