







MOLEX P/N	LENGTH	TOLERANCE (mm)	AWG	IMPEDANCE	EE SPEC	LABEL CONTEXT
2073701000	152mm	±10	32	100 OHMS	SAS 4.0	SAS4.0 100 Ohm
2073701001	300mm	±10	32	100 OHMS	SAS 4.0	SAS4.0 100 Ohm
2073701002	1000mm	±15	32	100 OHMS	SAS 4.0	SAS4.0 100 Ohm
2073701003	500mm	±10	32	100 OHMS	SAS 4.0	SAS4.0 100 Ohm
2073701300	152mm	±10	32	100 OHMS	SAS 3.0	SAS3.0 100 Ohm
2073701301	300mm	±10	32	100 OHMS	SAS 3.0	SAS3.0 100 Ohm
2073701302	1000mm	±15	32	100 OHMS	SAS 3.0	SAS3.0 100 Ohm
207370130	500mm	±10	32	100 OHMS	SAS 3.0	SAS3.0 100 Ohm
2073721001	300mm	±10	32	85 OHMS	PCIe 4.0	PCIe4.0 85 Ohm
2073721002	1000mm	±15	32	85 OHMS	PCIe 4.0	PCIe4.0 85 Ohm
2073721003	500mm	±10	32	85 OHMS	PCIe 4.0	PCIe4.0 85 Ohm

NOTES:
1. MATERIAL:
   HOUSING - PC 94V-0 BLACK
   LATCH - STAINLESS STEEL
   EXPANDO - PET
   CABLE - SHIELD: ALUMNINIZED POLYESTER FOIL
   - SIGNAL PAIR : SILVER-COATED COPPER
   - DRAIN: TIN-COATED COPPER
   - CONFORMS TO VW1
   PCB - FR4 (HALOGEN FREE)
2. THIS PRODUCT CONFORMS TO THE MECHANICAL DIMENSIONING OF SFF-8654
3. RoHS COMPLIANT. NO EXEMPTIONS

DOCUMENT STATUS	P1	RELEASE DATE	2021/03/31 06:34:01

FUNCTIONAL SYMBOLS
FA = 0
FC = 0
FP = 0
DIVISIONAL SYMBOLS

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS: mm
SCALE: 5:1
GENERAL TOLERANCES (UNLESS SPECIFIED)
ANGULAR TOL ± 3.0 °
4 PLACES ±
3 PLACES ± 0.2
2 PLACES ± 0.3
1 PLACE ± 0.4
0 PLACES ±
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC:
EC NO: 659680
DRWN: SMALLESHAPPA 2021/03/31
CHK'D: DSUN15 2021/03/31
APPR: VPENG01 2021/03/31
INITIAL REVISION:
DRWN: LOU01 2018/06/28
APPR: VPENG01 2018/08/13

THIRD ANGLE PROJECTION
DRAWING: D-SIZE
SERIES: 207370
MATERIAL NUMBER: SEE P/N TABLE
CUSTOMER: GENERAL MARKET
SHEET NUMBER: 1 OF 3

molex

SLIMSAS 4X STR TO RAD CABLE ASSY.

PRODUCT CUSTOMER DRAWING


DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
2073701000	PSD	000	D

PINOUT DIAGRAM

P1		SIGNAL TYPE	P2	
GND	A1	———	B1	GND
RX0+	A2	<———	B2	TX0+
RX0-	A3	<———	B3	TX0-
GND	A4	———	B4	GND
RX1+	A5	<———	B5	TX1+
RX1-	A6	<———	B6	TX1-
GND	A7	———	B7	GND
SB	A8	<———>	B8	SB
SB	A9	<———>	B9	SB
SB	A10	<———>	B10	SB
SB	A11	<———>	B11	SB
SB	A12	<———>	B12	SB
GND	A13	———	B13	GND
RX2+	A14	<———	B14	TX2+
RX2-	A15	<———	B15	TX2-
GND	A16	———	B16	GND
RX3+	A17	<———	B17	TX3+
RX3-	A18	<———	B18	TX3-
GND	A19	———	B19	GND
GND	B1	———	A1	GND
TX0+	B2	———>	A2	RX0+
TX0-	B3	———>	A3	RX0-
GND	B4	———	A4	GND
TX1+	B5	———>	A5	RX1+
TX1-	B6	———>	A6	RX1-
GND	B7	———	A7	GND
SB	B8	<———>	A8	SB
SB	B9	<———>	A9	SB
SB	B10	<———>	A10	SB
SB	B11	<———>	A11	SB
SB	B12	<———>	A12	SB
GND	B13	———	A13	GND
TX2+	B14	———>	A14	RX2+
TX2-	B15	———>	A15	RX2-
GND	B16	———	A16	GND
TX3+	B17	———>	A17	RX3+
TX3-	B18	———>	A18	RX3-
GND	B19	———	A19	GND


———> = TRANSMIT TO RECEIVE ON HIGH SPEED CIRCUITS
——— = GND
<———> = SIDEBAND
NOTE: ALL SIGNAL GROUND ARE BUSSED IN PCB.

P1




VIEW FROM MATING END OF THE CONNECTOR

P2



VIEW FROM MATING END OF THE CONNECTOR

LABEL DETAIL



MOLEX P/N
EE SPEC IMPEDANCE
(SEE "LABEL CONTEXT" ON P/N TABLE)

YY - LAST TWO DIGITS OF THE YEAR
WW - WEEK OF THE YEAR
SSSS - PRODUCTION BATCH OF THE WEEK

FONT: ARIAL
HEIGHT: 2mm Min.

DOCUMENT STATUS	P1	RELEASE DATE	2021/03/31 06:34:01

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

FUNCTIONAL SYMBOLS
FA = 0
FC = 0
FP = 0
DIVISIONAL SYMBOLS

DIMENSION UNITS	SCALE
mm	1:1

GENERAL TOLERANCES (UNLESS SPECIFIED)

ANGULAR TOL	±	3.0 °
4 PLACES	±	
3 PLACES	±	0.2
2 PLACES	±	0.3
1 PLACE	±	0.4
0 PLACES	±	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC:

EC NO: 659680
DRWN: SMALLESHAPPA 2021/03/31
CHK'D: DSUN15 2021/03/31
APPR: VPENG01 2021/03/31

INITIAL REVISION:
DRWN: LOU01 2018/06/28
APPR: VPENG01 2018/08/13

THIRD ANGLE PROJECTION | DRAWING: D-SIZE | SERIES: 207370

molex

SLIMSAS 4X STR TO RAD CABLE ASSY.

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
2073701000	PSD	000	D

MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
SEE P/N TABLE	GENERAL MARKET	2 OF 3

REVISION TABLE			
DATE	REV	DESCRIPTION	ENGINEER
2020/07/17	C	ADDED THE 500MM LENGTH P/N TO THE P/N TABLE	SACHIN M K
2021/03/31	D	SHEET 1: UPDATED THE SLIMSAS 4X STR MODEL TO THE LATEST VERSION	SACHIN M K

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

FUNCTIONAL SYMBOLS
FA = 0
FC = 0
FP = 0

DIVISIONAL SYMBOLS

DIMENSION UNITS	SCALE
mm	1:1

GENERAL TOLERANCES (UNLESS SPECIFIED)

ANGULAR TOL	±	3.0 °
4 PLACES	±	
3 PLACES	±	0.2
2 PLACES	±	0.3
1 PLACE	±	0.4
0 PLACES	±	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC:

EC NO: 659680
DRWN: SMALLESHAPPA 2021/03/31
CHK'D: DSUN15 2021/03/31
APPR: VPENG01 2021/03/31

INITIAL REVISION:
DRWN: LOU01 2018/06/28
APPR: VPENG01 2018/08/13

molex

SLIMSAS 4X STR TO RAD CABLE ASSY.

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
2073701000	PSD	000	D

THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
	D-SIZE	207370	SEE P/N TABLE	GENERAL MARKET	3 OF 3

DOCUMENT STATUS	P1	RELEASE DATE	2021/03/31 06:34:01

THIRD ANGLE PROJECTION
REVISION: J
DATE: 2020/07/16