


**Note**

- ① - Contact livré non assemblé  
*Contact delivered unassembled*
- ② - Cable compatible: Belden 1855A  
*Cable compatible: Belden 1855A*
- ③ - Outil de sertissage:  
Contact intérieur M22520/2-01 avec positionneur M22520/2-35(5)  
Contact extérieur M22520/5-01 avec positionneur M22520/5-05B
- ④ - Crimping tool:  
Inner contact M22520/2-01 with positioner M22520/2-35(5)  
Outer contact M22520/5-01 with positioner M22520/5-05B
- ⑤ - Matières:  
- Contact extérieur: inox  
- Contact intermédiaire: alliage de cuivre  
- Contact intérieur, fut de sertissage et ferule: laiton  
- Isolants: PTFE ou équivalent  
*Material*  
- Outer contact: Stainless steel  
- Intermediary contact: copper alloy  
- Inner contact, crimping barrel and ferrule: brass  
- Inserts: PTFE or equivalent
- ⑥ - Traitements:  
- Contact extérieur: passivation  
- Contact intermédiaire, intérieur, fut de sertissage et ferrule: dorure  
*Finish*  
- Outer contact: passivation  
- Intermediary and inner contact, crimping barrel and ferrule: Gold

<b>Douille coax T8 75 ohms 6G - SDI</b> <b>Socket coax S8 75 ohms 6G-SDI</b> <b>Ref: 612355</b>			
DRAWN BY: M.PRUD'HOM	UPDATED BY: M.LAINE	LAST APPROVED BY: L.LAGRANGE	
ALL DIMENSIONS ARE IN MM	<b>AMPHENOL SOCAPEX</b>		ORIGINAL DRAWING DATE: 30/10/20
SCALE: 7	B.P. 29 74311 THYEZ CEDEX		CONFIGURATION DATA ARE AVAILABLE IN PDM
		REV: B	PAGE: 1/1
<b>172-PLC-251-00</b>			

IN THE CONSTANT PURPOSE OF IMPROVING ITS PRODUCTS, Amphenol Socapex RESERVES THE RIGHT TO MODIFY ANY DIMENSION OR CHARACTERISTICS.  
FM.NPD.0036.THYZE.PUNE rev C