



**Note:**

- ① - Contact livré non assemblé  
*Contact delivered unassembled*
- ② - Cable compatible: CXN3671  
*Cable compatible: CXN3671*
- ③ - Outil de sertissage:  
Contact intérieur TBD  
Contact extérieur TBD  
*Crimping tool:*  
Inner contact TBD  
Outer contact TBD
- ④ - Matières:  
- Contacts extérieurs: inox  
- Contact intermédiaire: alliage de cuivre  
- Contact intérieur, fut de sertissage et ferrule: laiton  
- Isolants: PTFE ou équivalent  
*Material:*  
- Outer contact: Stainless steel  
- Intermediary contact: copper alloy  
- Inner contact, crimping barrel and ferrule: brass  
- Inserts: PTFE or equivalent
- ⑤ - Traitements:  
- Contact extérieur: passivation  
- Contact intermédiaire, intérieur, fut de sertissage et ferrule: dorure  
*Finish:*  
- Outer contact: passivation  
- Intermediary and inner contact, crimping barrel and ferrule: gold

<b>Douille Coax T8 75 ohms 12G-SDI</b> <b>Socket Coax S8 75ohms 12G-SDI</b> <b>Ref : 612455</b>			
DRAWN BY : M.PRUD'HOM		UPDATED BY : M.LAINE	
		LAST APPROVED BY : L.LAGRANGE	
<small>ALL DIMENSIONS ARE IN MM</small> <small>SCALE : 6</small> 	<b>AMPHENOL SOCAPEX</b> B.P. 29 74311 THYEZ CEDEX		<small>ORIGINAL DRAWING DATE :</small> 24/02/21
			<small>CONFIGURATION DATA ARE AVAILABLE IN PDM</small> REV : B    PAGE : 1/1
<b>172-PLC-270-00</b>			

IN THE CONSTANT PURPOSE OF IMPROVING ITS PRODUCTS, Amphenol Socapex RESERVES THE RIGHT TO MODIFY ANY DIMENSION OR CHARACTERISTICS.  
 FM.NPD.0036.THYZE.PUNE rev C