

Low-Skew Quad Clock Driver


General Description

The 100315 contains four low skew differential drivers, designed for generation of multiple, minimum skew differential clocks from a single differential input. This device also has the capability to select a secondary single-ended clock source for use in lower frequency system level testing. The 100315 is a 300 Series redesign of the 100115 clock driver.

Features


- Low output to output skew (≤ 50 ps)
- Differential inputs and outputs
- Secondary clock available for system level testing
- 2000V ESD protection
- Voltage compensated operating range: $-4.2V$ to $-5.7V$
- Standard Microcircuit Drawing (SMD) 5962-9469601

Logic Diagram



10031901

Connection Diagram



10031902

| Pin Names | Description |
|--|--------------------------------------|
| CLKIN, $\overline{\text{CLKIN}}$ | Differential Clock Inputs |
| CLK ₁₋₄ , $\overline{\text{CLK}}_{1-4}$ | Differential Clock Outputs |
| TCLK | Test Clock Input (<i>Note 1</i>) |
| CLKSEL | Clock Input Select (<i>Note 1</i>) |

Note 1: TCLK and CLKSEL are single-ended inputs, with internal 50 k Ω pulldown resistors.

Truth Table

| CLKSEL | CLKIN | CLKIN | TCL K | CLK _N | $\overline{\text{CLK}}_{N}$ |
|--------|-------|-------|----------|------------------|-----------------------------|
| L | L | H | X | L | H |
| L | H | L | X | H | L |
| H | X | X | L | L | H |
| H | X | X | H | H | L |

L = Low Voltage Level
H = High Voltage Level
X = Don't Care

Absolute Maximum Ratings *(Note 2)*

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Above which the useful life may be impaired

| | |
|--|-------------------|
| Storage Temperature | -65°C to +150°C |
| Maximum Junction Temperature (T_J) | |
| Ceramic | +175°C |
| Case Temperature under Bias (T_C) | -55°C to +125°C |
| V_{EE} Pin Potential to Ground Pin | -7.0V to +0.5V |
| Input Voltage (DC) | V_{CC} to +0.5V |
| Output Current (DC Output HIGH) | -50 mA |
| Operating Range (Note 2) | -5.7V to -4.2V |
| ESD (Note 3) | ≥2000V |

Recommended Operating Conditions

| | |
|-----------------------------|-----------------|
| Case Temperature (T_C) | |
| Military | -55°C to +125°C |
| Supply Voltage (V_{EE}) | -5.7V to -4.2V |

Note 2: Absolute maximum ratings are those values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 3: ESD testing conforms to MIL-STD-883, Method 3015.

Military Version DC Electrical Characteristics

$V_{EE} = -4.2V$ to $-5.7V$, $V_{CC} = V_{CCA} = GND$ (Note 6)

| Symbol | Parameter | Min | Typ | Max | Units | T_C | Conditions | Notes | |
|-----------|---------------------|-------|-----|-------|-------|---------------|--|---------------------------|--------------------------|
| V_{OH} | Output HIGH Voltage | -1025 | | -870 | mV | 0°C to +125°C | $V_{IN} = V_{IH(Max)}$ or $V_{IL(Min)}$ | Loading with 50Ω to -2.0V | (Note 4, Note 5, Note 6) |
| | | -1085 | | -870 | mV | -55°C | | | |
| V_{OL} | Output LOW Voltage | -1830 | | -1620 | mV | 0°C to +125°C | $V_{IN} = V_{IH(Min)}$ or $V_{IL(Max)}$ | Loading with 50Ω to -2.0V | (Note 4, Note 5, Note 6) |
| | | -1830 | | -1555 | mV | -55°C | | | |
| V_{OHC} | Output HIGH Voltage | -1035 | | | mV | 0°C to +125°C | $V_{IN} = V_{IH(Min)}$ or $V_{IL(Max)}$ | Loading with 50Ω to -2.0V | (Note 4, Note 5, Note 6) |
| | | -1085 | | | mV | -55°C | | | |
| V_{OLC} | Output LOW Voltage | | | -1610 | mV | 0°C to +125°C | $V_{IN} = V_{IH(Min)}$ or $V_{IL(Max)}$ | Loading with 50Ω to -2.0V | (Note 4, Note 5, Note 6) |
| | | | | -1555 | mV | -55°C | | | |

DC Electrical Characteristics

$V_{EE} = -4.2V$ to $-5.7V$, $V_{CC} = V_{CCA} = GND$ (Note 6)

| Symbol | Parameter | Min | Typ | Max | Units | T_C | Conditions | Notes |
|------------|---|----------------|-----|----------------|---------|---------------------------------|---------------------------------------|----------------------------------|
| V_{DIFF} | Input Voltage Differential | 150 | | | mV | $-55^\circ C$ to $+125^\circ C$ | Required for Full Output Swing | (Note 4, Note 5, Note 6) |
| V_{CM} | Common Mode Voltage | $V_{CC} - 2.0$ | | $V_{CC} - 0.5$ | V | $-55^\circ C$ to $+125^\circ C$ | | (Note 4, Note 5, Note 6) |
| V_{IH} | Single-Ended Input High Voltage | -1165 | | -870 | mV | $-55^\circ C$ to $+125^\circ C$ | Guaranteed HIGH Signal for All Inputs | (Note 4, Note 5, Note 6, Note 7) |
| V_{IL} | Single-Ended Input Low Voltage | -1830 | | -1475 | mV | $-55^\circ C$ to $+125^\circ C$ | Guaranteed LOW Signal for All Inputs | (Note 4, Note 5, Note 6, Note 7) |
| I_{IH} | Input HIGH Current CLKIN, \overline{CLKIN} | | | 150 | μA | $-55^\circ C$ to $+125^\circ C$ | $V_{IN} = V_{IH(Max)}$ | (Note 4, Note 5, Note 6) |
| | TCLK | | | 450 | μA | | | |
| | CLKSEL | | | 380 | μA | | | |
| I_{CBO} | Input Leakage Current | -10 | | | μA | $-55^\circ C$ to $+125^\circ C$ | $V_{IN} = V_{EE}$ | (Note 4, Note 5, Note 6) |
| I_{EE} | Power Supply Current, Normal | -80 | | -25 | mA | $-55^\circ C$ to $+125^\circ C$ | | (Note 4, Note 5, Note 6) |

Note 4: F100K 300 Series cold temperature testing is performed by temperature soaking (to guarantee junction temperature equals $-55^\circ C$), then testing immediately without allowing for the junction temperature to stabilize due to heat dissipation after power-up. This provides "cold start" specs which can be considered a worst case condition at cold temperatures.

Note 5: Screen tested 100% on each device at $-55^\circ C$, $+25^\circ C$, and $+125^\circ C$, Subgroups 1, 2, 3, 7, and 8.

Note 6: Sample tested (Method 5005, Table I) on each manufactured lot at $-55^\circ C$, $+25^\circ C$, and $+125^\circ C$, Subgroups A1, 2, 3, 7, and 8.

Note 7: Guaranteed by applying specified input condition and testing V_{OH}/V_{OL} .

AC Electrical Characteristics

$V_{EE} = -4.2V$ to $-5.7V$, $V_{CC} = V_{CCA} = GND$

| Symbol | Parameter | $T_C = -55^\circ C$ | | $T_C = +25^\circ C$ | | $T_C = +125^\circ C$ | | Units | Conditions | Notes |
|-------------|--|---------------------|------|---------------------|------|----------------------|------|-------|--------------|---------------------------|
| | | Min | Max | Min | Max | Min | Max | | | |
| t_{PLH} | Propagation Delay CLKIN, \overline{CLKIN} to $CLK_{(1-4)}$, $\overline{CLK}_{(1-4)}$ | 0.58 | 0.88 | 0.63 | 0.88 | 0.72 | 1.02 | ns | Figures 1, 2 | (Note 8, Note 9, Note 10) |
| t_{PHL} | | | | | | | | | | |
| t_{PLH} | Propagation Delay, TCLK to $CLK_{(1-4)}$, $\overline{CLK}_{(1-4)}$ | 0.30 | 1.60 | 0.30 | 1.50 | 0.40 | 1.70 | ns | | |
| t_{PHL} | | | | | | | | | | |
| t_{S-G-G} | Skew Gate to Gate (Note 12) | | 120 | | 100 | | 120 | ps | | (Note 10) |
| t_{TLH} | Transition Time 20% to 80%, 80% to 20% | 0.30 | 0.90 | 0.25 | 0.85 | 0.20 | 0.85 | ns | | |
| t_{THL} | | | | | | | | | | |


Note 8: F100K 300 Series cold temperature testing is performed by temperature soaking (to guarantee junction temperature equals $-55^\circ C$), then testing immediately after power-up. This provides "cold start" specs which can be considered a worst case condition at cold temperatures.

Note 9: Screen tested 100% on each device at $+25^\circ C$ temperature only, Subgroup A9.

Note 10: Sample tested (Method 5005, Table I) on each manufactured lot at $+25^\circ C$, Subgroup A9, and at $+125^\circ C$ and $-55^\circ C$ temperatures, Subgroups A10 and A11.

Note 11: Not tested at $+25^\circ C$, $+125^\circ C$ and $-55^\circ C$ temperature (design characterization data).


Note 12: Maximum output skew for any one device.



- Note 13:** Shown for testing CLKIN to CLK1 in the differential mode.
- Note 14:** L1, L2, L3 and L4 = equal length 50Ω impedance lines.
- Note 15:** All unused inputs and outputs are loaded with 50Ω in parallel with ≤ 3 pF to GND.
- Note 16:** Scope should have 50Ω input terminator internally.

10031903

FIGURE 1. AC Test Circuit



10031904

FIGURE 2. Propagation Delay, TCLK, CLKSEL to Outputs





FIGURE 3. Propagation Delay, CLKIN/CLKIN to Outputs




Note 17: The output to output skew, which is defined as the difference in the propagation delays between each of the four outputs on any one 100115 shall not exceed 75 ps.

FIGURE 4. Transition Times

OBSOLETE

Physical Dimensions inches (millimeters) unless otherwise noted



**16 Lead Ceramic Flatpak (F)
NS Package Number W16A**

OBSOLETE

Notes

100315

OBSOLETE

Notes

For more National Semiconductor product information and proven design tools, visit the following Web sites at:

| Products | | Design Support | |
|--------------------------------|--|------------------------------|--|
| Amplifiers | www.national.com/amplifiers | WEBENCH® Tools | www.national.com/webench |
| Audio | www.national.com/audio | App Notes | www.national.com/appnotes |
| Clock and Timing | www.national.com/timing | Reference Designs | www.national.com/refdesigns |
| Data Converters | www.national.com/adc | Samples | www.national.com/samples |
| Interface | www.national.com/interface | Eval Boards | www.national.com/evalboards |
| LVDS | www.national.com/lvds | Packaging | www.national.com/packaging |
| Power Management | www.national.com/power | Green Compliance | www.national.com/quality/green |
| Switching Regulators | www.national.com/switchers | Distributors | www.national.com/contacts |
| LDOs | www.national.com/ldo | Quality and Reliability | www.national.com/quality |
| LED Lighting | www.national.com/led | Feedback/Support | www.national.com/feedback |
| Voltage Reference | www.national.com/vref | Design Made Easy | www.national.com/easy |
| PowerWise® Solutions | www.national.com/powerwise | Solutions | www.national.com/solutions |
| Serial Digital Interface (SDI) | www.national.com/sdi | Mil/Aero | www.national.com/milaero |
| Temperature Sensors | www.national.com/tempensors | SolarMagic™ | www.national.com/solarmagic |
| Wireless (PLL/VCO) | www.national.com/wireless | PowerWise® Design University | www.national.com/training |

THE CONTENTS OF THIS DOCUMENT ARE PROVIDED IN CONNECTION WITH NATIONAL SEMICONDUCTOR CORPORATION ("NATIONAL") PRODUCTS. NATIONAL MAKES NO REPRESENTATIONS OR WARRANTIES WITH RESPECT TO THE ACCURACY OR COMPLETENESS OF THE CONTENTS OF THIS PUBLICATION AND RESERVES THE RIGHT TO MAKE CHANGES TO SPECIFICATIONS AND PRODUCT DESCRIPTIONS AT ANY TIME WITHOUT NOTICE. NO LICENSE, WHETHER EXPRESS, IMPLIED, ARISING BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT.

TESTING AND OTHER QUALITY CONTROLS ARE USED TO THE EXTENT NATIONAL DEEMS NECESSARY TO SUPPORT NATIONAL'S PRODUCT WARRANTY. EXCEPT WHERE MANDATED BY GOVERNMENT REQUIREMENTS, TESTING OF ALL PARAMETERS OF EACH PRODUCT IS NOT NECESSARILY PERFORMED. NATIONAL ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR BUYER PRODUCT DESIGN. BUYERS ARE RESPONSIBLE FOR THEIR PRODUCTS AND APPLICATIONS USING NATIONAL COMPONENTS. PRIOR TO USING OR DISTRIBUTING ANY PRODUCTS THAT INCLUDE NATIONAL COMPONENTS, BUYERS SHOULD PROVIDE ADEQUATE DESIGN, TESTING AND OPERATING SAFEGUARDS.

EXCEPT AS PROVIDED IN NATIONAL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, NATIONAL ASSUMES NO LIABILITY WHATSOEVER, AND NATIONAL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY RELATING TO THE SALE AND/OR USE OF NATIONAL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE CHIEF EXECUTIVE OFFICER AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

Life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness.

National Semiconductor and the National Semiconductor logo are registered trademarks of National Semiconductor Corporation. All other brand or product names may be trademarks or registered trademarks of their respective holders.

Copyright© 2009 National Semiconductor Corporation

For the most current product information visit us at www.national.com



www.national.com

**National Semiconductor
Americas Technical
Support Center**

Email: support@nsc.com
Tel: 1-800-272-9959

**National Semiconductor Europe
Technical Support Center**

Email: europe.support@nsc.com

**National Semiconductor Asia
Pacific Technical Support Center**

Email: ap.support@nsc.com

**National Semiconductor Japan
Technical Support Center**

Email: jpn.feedback@nsc.com