

Steward

Advanced Ferrite Materials, EMI Suppression, and Inductive Products

Home • Ferrite Product Lines • New Products • Technical • General • Contact • Steward Sales

CM1922X330R-00

| STEWARD PART NUMBERING SYSTEM | | | | | |
|-------------------------------|----------------|--------------------|----------------------|----------------|------------------------|
| PRODUCT SERIES CODE | PART SIZE CODE | RATED CURRENT CODE | IMPEDANCE VALUE CODE | PACKAGING CODE | ADDITIONAL DESCRIPTION |
| CM | 1812 | U | 600 | R | - 00 |

Ambient Operating Temperature Range :-55°C to + 125°C




Figure #1

Drawing Figure

| |
|------------------|
| Figure Number |
| 1 |


Electrical Characteristics

| | | |
|--------------------|------------|------------------------|
| NET Z @ 100 MHz | DCR Max | Rated Current mA |
| 33 | 0.003 | 10000 |

Physical Dimensions

| | | | | | | | | | |
|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| A mm | B mm | C mm | D mm | E mm | A in | B in | C in | D in | E in |
| 4.70 | 5.60 | 2.85 | 2.24 | 0.58 | 0.185 | 0.220 | 0.112 | 0.088 | 0.023 |





Specifications, which provide more details for the correct use of the described products, are available upon request. All

specifications are subject to change without notice. For more information on any of the products listed above, please contact Steward customer service department at (800) 634-2673.

americas@steward.com

mexico@steward.com

europa@steward.com

asia@steward.com

Copyright© 2004 Steward, Inc.

Last Updated: 2/24/2004