

6

5

4

3

2

1

SPECIFICATION

A: MATERIAL:

1. HOUSING: NYLON 66 FLAMMABILITY, UL 94V-0
2. TERMINAL: COPPER ALLOY, TIN PLATED

B: CHARACTERISTICS:


1. RATING: 10A 250V~ NORTH AMERICA & EUROPE
2. INSULATION RESISTANCE: 100 MΩ MIN, AT 500 VDC
3. ELECTRIC STRENGTH: AC 2,000 V FOR 1 MINUTE

C: APPROVALS:





D: ORDERING INFORMATION:



P/N	PANEL THICKNESS
42R35A-3152-080	0.8 mm
42R35A-3152-100	1.0 mm
42R35A-3152-120	1.2 mm
42R35A-3152-150	1.5 mm
42R35A-3152-200	2.0 mm
42R35A-3152-300	3.0 mm



Panel Thickness Option
(0.8, 1.0, 1.2, 1.5, 2.0, 3.0 mm)



Panel Thickness Option
(0.8, 1.0, 1.2, 1.5, 2.0, 3.0 mm)



PANEL CUT-OUT

RoHS
COMPLIANT

REVISIONS

REV DATE CHANGE CHNG CHK APPR

TOLERANCE
UNLESS OTHERWISE SPECIFIED
X ± 1
X.X ± 0.4
X.XX ± 0.20

DRAWN BY PB DATE: 9/15/21
CHECK BY - DATE: -
APPR BY DATE:

Power Dynamics, Inc.

Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

PART: IEC 60320 C14 APPLIANCE INLET; 2 FUSE
SNAP IN PANEL MOUNT; 6.3mm QC TERMINALS

PART #: **42R35A-3152-XXX**

SHEET
1 of 1

SIZE: A ALL DIMENSIONS FOR REFERENCE ONLY
SCALE: NTS REF MODEL: 0717-2

REV: -

6

5

4

3

2

1