

(Längen der Steck- und Anschlußseite gelten für eingepreßte Steckverbinder)
(mating and termination length of contacts apply to pressed in connectors)

yp — A B C K L M N P Q R S T

Referenzebene Tiefe
datum plane depth

Steckbereich:
length for mating:

3,7 ± 0,2

13 ± 0,2

min. 6

14,5 ± 0,2

min. 7,5

16 ± 0,2

min. 9

Steckbereich:
length for mating:

Kontaktbelegung
contact loading

[illegible]

Technical drawing of a grid of holes on a plate. The grid is 10 columns by 6 rows. Dimensions are given in millimeters. A feature control symbol at the top left indicates a hole with a diameter of 0.6 mm and a positional tolerance of 0.05 mm. A feature control symbol at the top right indicates a hole with a diameter of 2 mm and a positional tolerance of 0.05 mm. The grid is labeled with 'Position' and 'Reihe' (row). The grid is labeled with '1' and '11' for columns and 'f' through 'z' for rows. The grid is labeled with '23' for the total width and '6 x 2 (=12)' for the total height. The grid is labeled with '10 x 2 (=20)' for the width of the hole pattern.

Empfohlener Lochaufbau und
weitere Informationen siehe: DS 17 00 110 0101
1 *recommended configuration of plated through holes
and further information see: DS 17 00 110 0101*

			All Dimensions in mm Original Size DIN A 3			Techn. Character.			Nicht tolerierte Maß Free size tolerances IEC 61076-4-101		
				Dat.	Name	Maßstab/Scale 2 : 1	har-bus HM Messerleiste Typ C 77pol., Anschlußlänge 3,7mm <i>har-bus HM male connector type C 77pol., termination length 3,7mm</i>				
35962	04.01.10	Hage.	Detail.	28.08.98	HL.						
34337	22.05.07	Hage.	Insp.	28.08.98	Wei.						
28487	04.01.01	HL.	Stand.								
26971	02.12.99	HL.	HARTING Electronics GmbH & Co. KG					TB 17 03 077 x201			Blatt/ page /
22849			D-32339 ESPELKAMP					Sub.			
Mod.	Dat.	Name									