

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

-,-

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

GP

00

P

LTR

DESCRIPTION

DATE

DWN

APVD




C

REV PER ECO-11-007678

11MAY2011

RG

DO



4. FINISHES:

CROWN: GOLD PLATED, .000030 MIN THICK
OVER NICKEL PLATED, .000040 MIN THICK.

INSERT: SILVER PLATED, .000200 MIN THICK,
OVER NICKEL PLATED, .000040 MIN THICK.

CONTACT: SILVER PLATED, .000200 MIN THICK,
OVER NICKEL PLATED, .000040 MIN THICK.

3. MATERIALS:

HOUSING: THERMOPLASTIC, GLASS REINFORCED, COLOR-BLACK
UL94V-0 FLAMMABILITY RATED

INSERT: ZINC ALLOY, CASTING

CROWN: COPPER ALLOY

CONTACT: BRASS ALLOY

2. ITEMS PROVIDED TO THIS SPECIFICATION SHALL BE IDENTIFIED
ON THE CONTAINER WITH THE FOLLOWING INFORMATION:
PART NUMBER & DATE CODE OF MANUFACTURE.

1. INTERCHANGEABILITY REQUIRE PRIOR TE APPROVAL AND
AUTHORIZATION BY REVISION TO THIS DRAWING.

5. A FIVE POUND (5lb) FORCE IS REQUIRED TO CORRECTLY
SEAT THE CONNECTOR WITH PLATED THRU HOLES
LESS THAN $\phi 0.040$ INCH.

6643276-1

PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 06/19/06

HA/GRZYBOWSKI

CHK

-

APVD 06/19/06

FLICKINGER

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

STE

TE Connectivity

NAME

ICCON, PIN, SIZE No.8 PARALLEL
SOLDER TAIL, 10 PIN FOOT PRINT
LOCKING STYLE, .470 PIN EXT

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3 00779

C-6643276

SCALE 4:1

SHEET 1 OF 1

REV C