




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.2 – .51 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

--	--



Extraction Force	62 Newton
Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	15.29 mm[.602 in]
Compatible Insulation Diameter Range	2.01 – 3 mm[.079 – .118 in]
Wire Size	.2 – .51 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	10000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2-2150690-1
[OCEAN_2.0_APPLICATOR-E-070F110F](#)

TE Part # 2-2150690-2
[OCEAN_2.0_APPLICATOR-E-070F110F](#)

TE Part # 2150690-1
[OCEAN_2.0_APPLICATOR-E-070F110F](#)

TE Part # 2150690-2
[OCEAN_2.0_APPLICATOR-E-070F110F](#)

TE Part # 7-2150690-7
[OCEAN_2.0_SPARE_PART_KIT-070F110F](#)

Also in the Series | FASTON 110

Crimp Terminal Housings(13)

Insertion & Extraction Tools(1)

PCB Terminals(21)

Quick Disconnects(172)

Customers Also Bought

TE Part #1393845-5
[RP821024](#)

TE Part #5-1393738-9
[V42254A6004G109=SUB D GEHAEUSE](#)

TE Part #165075
[P.G. WIRE PIN 16-14](#)

TE Part #6-1393738-0
[V42254A6004G115=SUB D GEHAEUSE](#)





TE Part #61314-6
CMNL SOK S/F 24-18 .0125AUPHBZ



TE Part #174197-1
FASTON .250 SERIES (6.3 MM)
HOUSING




TE Part #5390377-5
50 POS A/P PLUG 25 CL 30AU



TE Part #173795-E
IDCCS SMC 1,27 50 * AU AUI 300 PVC



TE Part #NB09206001
ATUM-12/4-0-50MM



TE Part #5-1768307-5
LBF-79292097C

Documents

Product Drawings

110 MINI FASTON,REC.,24-20 AWG,TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_150545-2_V.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_150545-2_V.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_150545-2_V.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

EB**General Application Specification for Open Barrel Terminals

English

Application Specification

English

Product Environmental Compliance

Product Compliance

English



Product Compliance

English

Agency Approvals

UL Report

English