

4

3

2

1

© - TE Connectivity. All Rights Reserved.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	F3	REVISED PER ECN-21-127537	23NOV2021	RK	CDS

BODY

CUERPO RECEPTACULO

SLEEVE

COBRE

9.300

[.366]

22.000 MAX

[.866]

ø 4.000 [.157] MAX

INSULATION AISLANTE

5.530

[.218]

4

ZONE C

INSULATION

AISLANTE

1. MATERIAL:

BODY: SEE TABLE

SLEEVE: COPPER PER ASTM B152

INSULATION: POLYAMIDE 6/6 (NYLON) PER ASTM D4066

MATERIAL:

CUERPO: VER TABLA

MANGA: COBRE POR ASTM B152

AISLAMIENTO: POLIAMIDA 6/6 (NYLON) POR ASTM D4066

2. FINISH:

BODY: TIN PLATE 0.002 [.000079]

MIN EXT THICK PER ASTM B545

SLEEVE: NONE

INSULATION COLOR: BLUE

TERMINAR:

CUERPO: HOJA DE HOJALATA 0.002 [.000079]

ESPEJOR MÍNIMO EXT. POR ASTM B545

MANGA: NINGUNA

COLOR DE AISLAMIENTO: AZUL

3. WIRE RANGE: 1.000 [.039]–2.000 [.079]mm² [17–14 AWG]

GAMA DE ALAMBRE: 1.000 [.039] –2.000 [.079] mm² [17–14 AWG]

4. DIMENSION APPLIES TO ZONE C FOR A DISTANCE OF 8.620 – 8.750 [.339 – .344]

LOOSE PIECE PIEZA SUELTA	100	BRASS PER ASTM B36 LATÓN POR ASTM B36	735159
PACKAGE TYPE TIPO DE PAQUETE	QTY CANTIDAD	BODY MATL. CUERPO MATL.	PART NUMBER NÚMERO DE PIEZA

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

0

1

2

3

4

PLC

PLC

PLC

PLC

PLC

± -

± -

± -

± 0.500 [.019]

± -

ANGLES

FINISH

± -

2

MATERIAL

SEE TABLE

DWN
RAVI S
15NOV2019

CHK
DANIEL ROHDE
15NOV2019

APVD
DANIEL ROHDE
15NOV2019

PRODUCT SPEC
—

APPLICATION SPEC
—

WEIGHT
—

TE

TE Connectivity

NAME

FULLY INSULATED FASTON RCPT 6.35 MM (BLUE)
RECEPTÁCULO FASTON 6.35 MM AISLADO (AZUL)

—

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-735159

—

CUSTOMER DRAWING

SCALE 5:1

SHEET 1 OF 1

REV F3

1470-19 (1/15)