



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Flag
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.3 mm[.012 in]
Product Length	12.06 mm[.475 in]
Compatible Insulation Diameter Range	1.52 – 2.31 mm[.06 – .091 in]
Wire Size	.32 – .82 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	4000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>





EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 60755-1 187 FASTON FLAG REC 20-16 AWG BR	 TE Part # 63848-1 187 FASTON FLAG REC 20-16 AWG BR	 TE Part # 63848-2 187 FASTON FLAG REC 20-16 AWG TPBR	 TE Part # 1855638-1 HDM/FA EAPR.070F.110F BENCH G /LM CUT
 TE Part # 1855638-2 HDM/FA EAPR.070F.110F BENCH K CUT	 TE Part # 2-4150019-1 OCEAN-2.0-APPLICATOR-E-070F110F	 TE Part # 2-4150019-2 OCEAN-2.0-APPLICATOR-E-070F110F	 TE Part # 4150019-1 OCEAN-2.0-APPLICATOR-E-070F110F
 TE Part # 687801-3 M EMPR070F110FK	 TE Part # 7-4150019-1 OCEAN-2.0-APPLICATOR-E-070F110F	 TE Part # 7-4150019-2 OCEAN-2.0-APPLICATOR-E-070F110F	 KIT TE Part # 7-4150019-7 OCEAN_2.0_SPARE_PART_KIT-070F110F
 TE Part # 4150019-2 OCEAN-2.0-APPLICATOR-E-070F110F	 TE Part # 687801-2 M EMPO070F110FT		



Also in the Series

FASTON 187

Crimp Terminal Housings(42)	Insertion & Extraction Tools(1)	Joints & Splices(1)	PCB Terminals(42)
Quick Disconnects(209)	Splices(1)		

Customers Also Bought

 TE Part #1717109-1 0.64 III 16POS PLUG ASSY	 TE Part #61375-1 250 FASTON REC 18-14 AWG TPBR	 TE Part #3-640108-1 AMP-IN, MINI 26-22 008PTLPHBZ	 TE Part #5-160555-2 110 FASTON REC 20-18 AWG TPBR
 TE Part #350566-7 MINI AMP-IN 22-18 AWG POST TIN PLTD	 TE Part #3-770565-2 MINI AMP-IN 22-18 AWG LF	 TE Part #62814-1 250 FASTON FLAG REC 22-18 AWG BR	 TE Part #62003-2 110 FASTON REC 22-18 AWG TPBR
 TE Part #1670804-1 MCON 2.8 TERMINAL - LL	 TE Part #929941-6 JPT REC 2.8 Contact SWS Ag		



Documents

Product Drawings

187 FASTON FLAG REC 22-18 AWG BR

English

CAD Files

Customer View Model

ENG_CVM_CVM_62085-1_P.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_62085-1_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_62085-1_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English