




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **2050 – 5180 CMA**

Mating Tab Width: **6.35 mm [.25 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
---------------------	--------

Electrical Characteristics

Voltage Rating	300 V
----------------	-------

Body Features

Insulation Material	Nylon
---------------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Piggyback
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Tin
Crimp Type	Compression



Barrel Type	Closed
-------------	--------

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Product Length	23.41 mm[.922 in]
Compatible Insulation Diameter Range	4.32 mm[.17 in]
Wire Size	2050 – 5180 CMA

Usage Conditions

Insulation Option	Partially Insulated
Operating Temperature Range	105 °C[221 °F]

Packaging Features

Packaging Quantity	500
Packaging Method	Box

Other

Barrel Color	Blue
--------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 58433-3 PRO CR ASSY, RBY IS9252	TE Part # 47387 DAHT PG PIDG 20-14 ASSY	TE Part # 58423-1 DIE, RBY IS9252	TE Part # 47387-7 DAHT PG PIDG 16-12 ASSY
TE Part # 539691-2 ERGO DIE R.B.Y	TE Part # 2063030-1 SDE DIESET, RBY, UL	TE Part # 169400 CERTI-LOK FRAME W/O DIES	TE Part # 1SET191001R0000 CRIMP-HT
TE Part # 2392022-2 BLUE BATTERY DAHT KIT 220V (47387-7)	TE Part # 2392022-1 BLUE BATTERY DAHT KIT 110V (47387-7)	TE Part # 169404 CERTI-LOK DIE	

Customers Also Bought



TE Part #NB-PTCO-058
Pt100, 2.0x2.3, Class T, PTFC101T1G0

TE Part #52937-1
TERMINAL,PIDG SPR SPD 16-14 10

TE Part #HDP26-18-21SN-L017
PLG, 21P, BLK, N, RNG, 20, S

TE Part #927843-2
.140 SOCKET

TE Part #160451-3
FF 250 TAB 18-14AWG PB SILVER PL LP

TE Part #34484
TERMINAL,SOLIS R 14-12 10

TE Part #2-1768404-6
LBG-U-02909/PM07507

TE Part #690472-6
STRIPPER

TE Part #3-1105050-1
HN.D-C-STI.AG.0,75

Documents

Product Drawings

FASTON, PGYBCK, PIDG, PH BR, .250, 16-14

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_9-160463-5_F2.2d_dxf.zip

English

Customer View Model

ENG_CVM_9-160463-5_F2.3d_igs.zip

English

Customer View Model

ENG_CVM_9-160463-5_F2.3d_stp.zip

English

3D PDF

3D



Customer View Model

[ENG_CVM_CVM_9-160463-5_S.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_9-160463-5_S.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_9-160463-5_S.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Environmental Compliance

[Product Compliance Document](#)

English

[Product Compliance Document](#)

English