



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.75 – 2.5 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.36 mm[.014 in]
Product Length	15.62 mm[.614 in]
Compatible Insulation Diameter Range	2.79 – 4.06 mm[.11 – .16 in]
Wire Size	.75 – 2.5 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	3500
Packaging Method	Strip/Reel

Other

Line	FASTON .187
------	-------------

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 2305570-1 Strip Terminal Cutter-Side Feed-No Crimp	 TE Part # 63524-1 187 FASTON TAB 18-14 AWG TPBZ	 TE Part # 2-2266748-1 OCEAN_2.0_Applicator-S-090F1800	 TE Part # 2-2266748-2 OCEAN_2.0_Applicator-S-090F1800
 TE Part # 2178549-2 187 FASTON,REC.,18-14 AWG,TPBR	 TE Part # 2266748-1 OCEAN_2.0_Applicator-S-090F1800	 TE Part # 2266748-2 OCEAN_2.0_Applicator-S-090F1800	 TE Part # 7-2266748-1 OCEAN_2.0_Applicator-S-090F1800
 TE Part # 7-2266748-2 OCEAN_2.0_Applicator-S-090F1800	 KIT TE Part # 7-2266748-7 OCEAN_2.0_SPARE_PART_KIT-090F1800		

Also in the Series | FASTON 187



Crimp Terminal Housings(42)



Insertion & Extraction Tools(1)



Joints & Splices(1)



PCB Terminals(42)




Quick Disconnects(209)




Splices(1)


Customers Also Bought




TE Part #640456-4
04P MTA100 HDR ASSY F/L SQ STR



TE Part #5-1775444-2
EMIX CONN., 1.5MM PITCH, HDR, R /A, 2P



TE Part #2176125-2
SQP20 10R 5% WIRE




TE Part #926869-3
UNIV-MNL SOCKET 1



TE Part #62109-1
250 FASTON REC 18-14 AWG BR




TE Part #1375819-1
CST-100 II CONTACT TIN PLT



TE Part #1-1586017-6
16P FH PLUG VAL-U-LOK V0



TE Part #703636-000
TTMS-19.0-4



TE Part #121444-000
TTMS-25.4-4

Documents



Product Drawings

187 FASTON,PIGGYBACK REC.,18-14 AWG,TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_1217151-1_E.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1217151-1_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1217151-1_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_1217151-1_03222018956_dmtec

English

MD_1217151-1_03222018956_dmtec

English

Agency Approvals

CSA Certificate

English

CSA Certificate

English