



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **1.31 – 3.31 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Terminal Material Thickness	.3 mm[.012 in]
Product Length	19.05 mm[.75 in]
Compatible Insulation Diameter Range	4.06 – 5.33 mm[.16 – .21 in]
Wire Size	1.31 – 3.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	10000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1-1579007-4 EXTRACTION TOOL	 TE Part # 4-1579007-3 EXTRACTION TOOL KIT	 TE Part # 2-2150487-1 OCEAN_2.0_APPLICATOR-E-120F250F	 TE Part # 2-2150487-2 OCEAN_2.0_APPLICATOR-E-120F250FA
 TE Part # 2150487-1 OCEAN_2.0_APPLICATOR-E-120F250F	 TE Part # 2150487-2 OCEAN_2.0_APPLICATOR-E-120F250FA	 TE Part # 7-2150487-1 OCEAN_2.0_APPLICATOR-E-120F250F	 TE Part # 7-2150487-2 OCEAN_2.0_APPLICATOR-E-120F250FA
 KIT REPRESENTATION ONLY TE Part # 7-2150487-7 OCEAN_2.0_SPARE_PART_KIT-120F250F			

Also in the Series | FASTIN-FASTON 250





Crimp Terminal Housings(211)



Insertion & Extraction Tools(2)



PCB Terminals(2)



Quick Disconnects(254)

Customers Also Bought



TE Part #2056350007
ES-CAP-NO.3-B8-0-50MM



TE Part #34072
SPLICE,PG BUTT 12-10



TE Part #770064-1
01P .093 COMM P&S PLUG HSG



TE Part #2-34173-1
TERMINAL,PG R 12-10 3/8




TE Part #61866-1
RING TERMINAL CRIMP 10-6 AWG
TPBR



TE Part #61795-6
RING 18-14 AWG TPBR



TE Part #W3S-1939-P012
WEDGE LOCK, 3P, PLG, BLU,SL RET,
J1939,DT



TE Part #936261-1
090 SLD TAB CONT(0.85-1.25)



TE Part #931901-000
2021D0309-0

Documents

Product Drawings
FF 250 REC 16-12AWG TPBR
English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_60253-2_BV_c-60253-2-bv.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_60253-2_BV_c-60253-2-bv.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_60253-2_BV_c-60253-2-bv.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[FASTIN_FASTON_Product_Line](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[MD_60253-2_06052018846_dmtec](#)

English

[MD_60253-2_06052018846_dmtec](#)

English