



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Silver
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

	.055 in
Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	28 mm[1.1 in]
Compatible Insulation Diameter Range	2.2 – 3.3 mm[.087 – .126 in]
Wire Size	.32 – .82 mm²

Usage Conditions

Insulation Option	Uninsulated
-------------------	-------------

Packaging Features

Packaging Quantity	3500
Packaging Method	Strip/Reel

Other

Terminals & Splices Comment	"According to DIN, except Wire Size Range", Tab for crimping Tab Housing Part No. 927203., With locking hole.
-----------------------------	---

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 91514-1
CCII FASTON 250 REC 22-18 ASSY

TE Part # 2-2150037-2
OCEAN_2.0_APPLICATOR-E-090F140F

TE Part # 2150037-2
OCEAN_2.0_APPLICATOR-E-090F140F

TE Part # 7-2150037-2
OCEAN_2.0_APPLICATOR-E-090F140F

TE Part # 7-2150037-7
OCEAN_2.0_SPARE_PART_KIT-090F140F

Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(211)

Insertion & Extraction Tools(2)

PCB Terminals(2)

Quick Disconnects(254)

Customers Also Bought



TE Part #1375618-1 06P DUAC STRAIN RELIEF	TE Part #794941-1 08P MINI UMNL CAP HSG	TE Part #794821-1 08P MINI UMNL PLUG HSG	TE Part #794805-1 4 CIR UMNL PLUG, ROUND HOLES
TE Part #794772-8 08P MINI UMNL SEAL, DIE CUT	TE Part #160655-2 FASTON 110 REC 20-15 AWG PTPB	TE Part #1586315-2 VAL-U-LOK SKT BR AU 24-18 LP	TE Part #626056 FASTIN-ON 110 HOUSING REC PA66 NATURAL
TE Part #794939-1 04P MINI UMNL CAP HSG	TE Part #1586019-6 6P RCPT VAL-U-LOK V0		

Documents

Product Drawings

FF 250 TAB 22-18AWG BR SILVER PLATED

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160691-5_Z.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160691-5_Z.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160691-5_Z.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Specifications

Application Specification

English