




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	19.12 mm[.753 in]
Compatible Insulation Diameter Range	3.1 – 4.3 mm[.12 – .17 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	12000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>








EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 58524-1 PROCRIMPER TOOL & DIE	 TE Part # 90165-1 DAHT 250 FASTON REC 18-14 ASSY	 TE Part # 42845-1 250 FASTON REC 18-14 AWG BR	 TE Part # 42845-2 250 FASTON REC 18-14 AWG TPBR
 TE Part # 58524-2 PROCRIMPER DIE	 TE Part # 2-2150016-1 OCEAN_2.0_Applicator-E-100F180F	 TE Part # 2-2150016-2 OCEAN_2.0_Applicator-E-100F180F	 TE Part # 2-2150440-1 OCEAN_2.0_Applicator-E-100F170OV
 TE Part # 2-2150440-2 OCEAN_2.0_Applicator-E-100F170OV	 TE Part # 2150016-1 OCEAN_2.0_Applicator-E-100F180F	 TE Part # 2150016-2 OCEAN_2.0_Applicator-E-100F180F	 TE Part # 2150440-1 OCEAN_2.0_Applicator-E-100F170OV
 TE Part # 2150440-2 OCEAN_2.0_Applicator-E-100F170OV	 TE Part # 7-2150016-1 OCEAN_2.0_Applicator-E-100F180F	 TE Part # 7-2150016-2 OCEAN_2.0_Applicator-E-100F180F	 TE Part # 7-2150016-7 OCEAN_2.0_SPARE_PART_KIT-100F180F



TE Part # 7-2150440-1
OCEAN_2.0_Applicator-E-100F170OV

TE Part # 7-2150440-2
OCEAN_2.0_Applicator-E-100F170OV

KIT
REPRESENTATION ONLY
TE Part # 7-2150440-7
OCEAN_2.0_SPARE_PART_KIT-100F170OV

Also in the Series

FASTON 250

Compression Connectors(4)

Crimp Terminal Housings(142)

Insertion & Extraction Tools(6)

Magnet Wire Terminals(1)

PCB Terminals(135)

Quick Disconnects(445)

Splices(4)

Customers Also Bought

TE Part #521368-2
ULTRA-POD 250 ASSY REC 22-18 AWG TPBR

TE Part #52454
PG SPR SPD 22-16COMM 22-18MIL8

TE Part #61944-1
250 FASTON REC 18-14 AWG BR

TE Part #63315-1
250 FASTON FLAG 18-14 AWG BR

TE Part #521411-1
ULTRA-POD 250 ASY REC 22-18 AWG BR

TE Part #9-794115-3
3P SL156 HSG W/LCK RAMP NATL #

TE Part #1-480487-2
FASTON 187 FLAG HSG NYLON NAT LP

TE Part #469004-1
FLOATING SHEAR



Documents

Product Drawings

250 FASTON REC 18-14 AWG BR

English

CAD Files

Customer View Model

ENG_CVM_CVM_42660-1_CM.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_42660-1_CM.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42660-1_CM.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance Document

English

Product Compliance Document

English

Agency Approvals

CSA Certificate

English

CSA Certificate



English