

10 9 8 7 6 5 4 3 2 1

MATERIAL NUMBER	ENGINEERING NUMBER	D2 MAX	B MAX	L MAX	E MIN	D1 MIN	D MAX
192030374	192030374	.079/2.00	.260/6.61	.721/18.32	.173/4.40	.083/2.10	.166/4.20

F

E

D

C

B

A

NOTES:

1. MATERIAL: STEEL, .031/0.80 THICK REF

2. FINISH: NICKEL PLATED WITH OPTIONAL COPPER FLASH UNDERPLATING, IS ALLOWED FOR IMPROVED ADHESION.

3. WIRE RANGE: 16-14

4. PART IS ROHS COMPLIANT.

5. AMBIENT OPERATING TEMPERATURE UP TO 900 °F (483 °C).

(C1)

DOCUMENT STATUS P1 RELEASE DATE 2022/06/02 15:20:38

9 8 7 6 5 4 3 2 1

FUNCTIONAL SYMBOLS

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS

SCALE

IN/MM NTS

CURRENT REV DESC: REMASTERED IN ECTR AND UPDATED NOTE

GENERAL TOLERANCES (UNLESS SPECIFIED)

MM INCH

4 PLACES ± ±

3 PLACES ± ±

2 PLACES ± ±

1 PLACE ± ±

0 PLACES ± ±

ANGULAR TOL ± °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

THIRD ANGLE PROJECTION

DRAWING

B-SIZE

SERIES

19203

MATERIAL NUMBER

SEE CHART

CUSTOMER

GENERAL MARKET

SHEET NUMBER

1 OF 1

EC NO: 708789

DRWN: PAWANC

CHK'D: DMYRICK

APPR: JMACNEIL

INITIAL REVISION:

DRWN: ASAYDEH

APPR: RDEROSS

05/12/02

05/12/02

DOCUMENT NUMBER

SD-19203-026

DOC TYPE

PSD

DOC PART

001

REVISION

C1

MALE CONNECTOR TERMINAL

KRIMPTITE, STEEL, 900 DEG F (483 DEG C)

PRODUCT CUSTOMER DRAWING

molex