




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.31 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------



Mechanical Attachment

Extraction Force	7 – 100 Newton
Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.3 mm[.012 in]
Product Length	19.18 mm[.755 in]
Compatible Insulation Diameter Range	2.29 – 3.3 mm[.09 – .13 in]
Wire Size	.51 – 1.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	UL
-----------------	----

Packaging Features

Packaging Quantity	12000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 63784-1 RCPT POS/LK 187 0126PTPBR	TE Part # 2-2150186-1 OCEAN_2.0_Applicator-E-090F180F	TE Part # 2-2150186-2 OCEAN_2.0_Applicator-E-090F180F	TE Part # 2150186-1 OCEAN_2.0_Applicator-E-090F180F
TE Part # 2150186-2 OCEAN_2.0_Applicator-E-090F180F	TE Part # 7-2150186-1 OCEAN_2.0_Applicator-E-090F180F	TE Part # 7-2150186-2 OCEAN_2.0_Applicator-E-090F180F	TE Part # 7-2150186-7 OCEAN_2.0_SPARE_PART_KIT-090F180F

Also in the Series | Mark II

Automotive Housings(7)	Automotive Terminals(22)	Crimp Terminal Housings(76)	Insertion & Extraction Tools(2)
Quick Disconnects(57)			



Also in the Series

Positive Lock 187

Crimp Terminal Housings(86)

Insertion & Extraction Tools(2)

Insulation Boots & Sleeves(7)

Quick Disconnects(55)

Customers Also Bought

TE Part #350550-6
UMNL SOK 20-14 AU/PHBZ L/P

TE Part #350547-6
UMNL PIN 20-14 AU/PHBZ L/P

TE Part #62191-1
110 FASTON REC 20-16 AWG TPBR

TE Part #40960
RING TERMINAL 14-12 AWG TPBR

TE Part #640748-7
HEAVY DUTY BURNER REC 18-14
AWG PHBRZ

TE Part #213845-3
POWERBAND CONT ASSY,SILVER PLT

TE Part #347874-1
CABLE SEAL LC SILICON 0.5 T

TE Part #63953-1
187 FASTON TAB

TE Part #1-173974-1
PL 187 HOUSING RECEPTACLE
NATURAL

TE Part #1108782-1
MDL2-GR.O-6.B1-3

Documents

Product Drawings

PL 187 RECEPTACLE 20-16 AWG TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_63195-1_AG.2d_dxf.zip



English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_63195-1_AG.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_63195-1_AG.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Positive Lock Receptacles](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[TE Material Declaration](#)

English