



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 3.31 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Flag
Contact Base Material	Steel
Terminal Plating Material	Nickel
Crimp Type	Tab-Lok
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	17.02 mm[.67 in]
Compatible Insulation Diameter Range	2.79 – 5.33 mm[.11 – .21 in]
Wire Size	.82 – 3.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 250 °C[-40 – 482 °F]

Industry Standards

Agency/Standard	RU (UL Component Program), UL
Approved Standards	UL E66717

Packaging Features

Packaging Quantity	3500
Packaging Method	Strip/Reel

Other

Line	Premier
Terminals & Splices Comment	Stress Relieved.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1969507-9 250 FASTON HSG.,FLAG,REC.,1 POS, NATRUAL	 TE Part # 2238142-1 250 FASTON,FLAG,REC.,22-16 AWG, NPST	 TE Part # 1969507-2 250 FASTON HSG.,FLAG,REC.,1 POS, NATRUAL	 TE Part # 1852633-1 EAPOHB160TABLOCK180O LM/G-HINGE BAR
 TE Part # 1852895-1 HDM EMPO K-HINGE BAR	 TE Part # 2390747-1 250 FASTON FLAG HOUSING 1P, NAT	 TE Part # 2390748-1 250 FASTON FLAG HOUSING 2P, NAT	 TE Part # 2390748-2 250 FASTON FLAG HOUSING 2P, BLUE
 TE Part # 2390748-3 250 FASTON FLAG HOUSING 2P, RED	 TE Part # 687395-6 HDM HBEAPR160T180OTSA	 TE Part # 565504-1 STD HBEMPR160T180OK	 TE Part # 565504-3 STD HBEMPR160T220OK

Also in the Series | FASTON 250



Compression Connectors(4)



Crimp Terminal Housings(142)



Insertion & Extraction Tools(6)



Magnet Wire Terminals(1)



PCB Terminals(135)



Quick Disconnects(445)



Splices(4)


Customers Also Bought



TE Part #1971782-2
PTL TAB CONTACT, 14 AWG




TE Part #2238041-1
187 FASTON,REC.,20-16 AWG,NPST



TE Part #154718-1
250 PL MKI REC. 18-14AWG BR



TE Part #63604-1
250 FASTON FLAG REC 18-12 AWG NPST



TE Part #640748-7
HEAVY DUTY BURNER REC 18-14 AWG PHBRZ



TE Part #1742883-1
187 FASTON,REC.,20-16 AWG,NPST



TE Part #322447
TERMINAL,SOLIS R 12-10 4



TE Part #1969507-2
250 FASTON HSG.,FLAG,REC.,1 POS, NATRUAL



TE Part #1969726-1
2P HEAVY DUTY BURNER HSG

Documents



Product Drawings

250 FASTON,FLAG,REC.,18-12 AWG,NPST

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1742543-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1742543-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1742543-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

1-1773948-2 Standard Line FASTON Receptacles QRG

English

Introductory Flyer - Low Insertion Force FASTON Terminals

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English