




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Terminal Material Thickness	.3 mm[.012 in]
Product Length	21.46 mm
Compatible Insulation Diameter Range	1.52 – 2.54 mm[.06 – .1 in]
Wire Size	.32 – .82 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	12000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1-1579007-4 EXTRACTION TOOL	 TE Part # 4-1579007-3 EXTRACTION TOOL KIT	 TE Part # 2-2150254-1 OCEAN_2.0_APPLICATOR-E-090F1000	 TE Part # 2-2150254-2 OCEAN_2.0_APPLICATOR-E-090F1000A
 TE Part # 2150254-1 OCEAN_2.0_APPLICATOR-E-090F1000	 TE Part # 2150254-2 OCEAN_2.0_APPLICATOR-E-090F1000A	 TE Part # 2217747-1 CCII FASTIN-FASTON 22-18 ASSY	 TE Part # 7-2150254-1 OCEAN_2.0_APPLICATOR-E-090F1000
 TE Part # 7-2150254-2 OCEAN_2.0_APPLICATOR-E-090F1000A	 TE Part # 7-2150254-7 OCEAN_2.0_SPARE_PART_KIT-090F1000		

Also in the Series | FASTIN-FASTON 250



Crimp Terminal Housings(211)

Insertion & Extraction Tools(2)

PCB Terminals(2)

Quick Disconnects(254)

Customers Also Bought

TE Part #8-34124-1
TERM,SOLIS R 16-14 1/4

TE Part #326741
TERMINAL,PG SPD 16-14 8

TE Part #1-33220-2
TERMINAL,SOLIS R 12-10 3/8

TE Part #61626-2
.140 DIA SOK 20-14 PTPPHBZ

TE Part #61867-2
RING CRIMP 18-14 AWG TPBR

TE Part #42100-2
FF 250 REC 18-14AWG TPBR

TE Part #DT04-12PC-BL04
REC, 12P, GRN, N, ENH KEY, FLANGE, C

TE Part #61868-1
RING CRIMP 10-6 AWG TPBR

TE Part #521227-2
ULTRA-POD 250 ASSY TAB 12-10 AWG TPBR

TE Part #EK5194-000
ES2000-NO.6-H2-0-39MM

Documents

Product Drawings
FF 250 REC 22-18AWG TPBR

English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_60413-1_AH.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_60413-1_AH.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_60413-1_AH.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[FASTIN_FASTON_Product_Line](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[TE Material Declaration](#)

English