




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	19.05 mm[.75 in]
Compatible Insulation Diameter Range	3.1 – 4.3 mm[.12 – .17 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	10000
Packaging Method	Strip/Reel

Other

Line	Budget
------	--------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 58524-1 PROCRIMPER TOOL & DIE	TE Part # 42845-1 250 FASTON REC 18-14 AWG BR	TE Part # 42845-2 250 FASTON REC 18-14 AWG TPBR	TE Part # 58524-2 PROCRIMPER DIE
TE Part # 2-2150016-1 OCEAN_2.0_Applicator-E-100F180F	TE Part # 2-2150016-2 OCEAN_2.0_Applicator-E-100F180F	TE Part # 2150016-1 OCEAN_2.0_Applicator-E-100F180F	TE Part # 2150016-2 OCEAN_2.0_Applicator-E-100F180F
TE Part # 7-2150016-1 OCEAN_2.0_Applicator-E-100F180F	TE Part # 7-2150016-2 OCEAN_2.0_Applicator-E-100F180F	TE Part # 7-2150016-7 OCEAN_2.0_SPARE_PART_KIT-100F180F	

Also in the Series | FASTON 250



 Compression Connectors(4)	 Crimp Terminal Housings(142)	 Insertion & Extraction Tools(6)	 Magnet Wire Terminals(1)
 PCB Terminals(135)	 Quick Disconnects(445)	 Splices(4)	

Customers Also Bought

 TE Part #5-2232263-4 PTL 1X4 CAP PANEL MT GLW WIRE KEY A DGR	 TE Part #41727 250 FASTON REC 16-12 AWG BR	 TE Part #42617-1 187 FASTON REC 20-16 AWG BR	 TE Part #1863011-1 01P UMNL PLUG HSG
 TE Part #5-2232266-3 PTL 2X3 PLUG HSG GLW WIRE KEY A DGR	 TE Part #1863012-1 01P UMNL CAP HSG	 TE Part #62011-1 250 FASTON FLAG REC 12-10 AWG BR	 TE Part #1241959-4 STD-TIM HSG MKII 4P
 TE Part #60635-3 250 FASTON REC 14-10 AWG BR	 TE Part #60650-1 250 FASTON FLAG REC 18-14 AWG BR		

Documents



Product Drawings

250 FASTON REC 18-14 AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_42400-1_BN.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_42400-1_BN.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42400-1_BN.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_42400-1_121620152114_dmtec

English

MD_42400-1_121620152114_dmtec

English

Agency Approvals

CSA Certificate

English

CSA Certificate

English