

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

E2

REVISED PER ECO-11-004820

11MAR11

RK

HMR

AMP
WIRE RANGE

FILE
E66717

LR7189
Certified

22-18 AWG
STRANDED

22-18 AWG
STRANDED

22-18 AWG
STRANDED

1

AMP

22-18

.375 REF

.891 MAX

3

.016±.001

.21 REF

1

2

3

4

5

MARKED AMP 22-18

DESIGNED FOR WIRE INSULATION DIA OF .090-.125.

MATES WITH .250±.003 BY .032±.001 THK TAB.

BODY: BRASS, TIN PLATED SLEEVE: NYLON, RED

RATED FOR 10 MAX AMPERE

TE CONNECTIVITY
CUSTOMER SERVICE SYSTEM

FOR ADDITIONAL
PRODUCT INFORMATION OR
COPIES OF DRAWING
AND TECHNICAL DOCUMENTS

FOR APPLICATION
TOOLING INFORMATION

FOR ORDER ENTRY

PRODUCT INFORMATION CENTER
1-800-522-6752

TOOLING ASSISTANCE CENTER
1-800-722-1111

1-800-526-5142

MAX RECOMMENDED OPERATING
TEMPERATURE:
105°C [221°F]
-

VOLTAGE RATING:
300V MAX
-

CIRCULAR MIL AREA:
509-1,900
STRANDED

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± .008

4 PLC ± -

ANGLES ± -

FINISH

MATERIAL

- 4

DWN
JR RUTH
CHK
T MICHIELUTTI
APVD
T MICHIELUTTI
PRODUCT SPEC
-
APPLICATION SPEC
114-13076
WEIGHT
-

07NOV01
07NOV01
07NOV01

RECEPTACLE, 250 SERIES, FASTON,
FULLY INSULATED, WIRE: 22-18 AWG

SIZE
A3

CAGE CODE
00779

DRAWING NO
C-696357

RESTRICTED TO
-

CUSTOMER DRAWING

SCALE
1:1

SHEET
1 OF 1

REV
E2

100

LOOSE PIECE

8-696357-1

1000

LOOSE PIECE

696357-1

QTY

PACKAGE TYPE

PART NO.

1470-19 (3/11)