

4		3		2		1			
THIS DRAWING IS UNPUBLISHED.				RELEASED FOR PUBLICATION ,19 .					
© COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.									
LOC		DIST		REVISIONS					
G		14		P	LTR	DESCRIPTION	DATE	DWN	APVD
				G		REV PER 0G3A-0176-02	08APR02	JR	TM

1. INSULATION DIA .082 MAX

2. FITS TAB .020±.001

AMP INCORPORATED CUSTOMER SERVICE SYSTEM		MAX RECOMMENDED OPERATING TEMPERATURE: -		THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		DWN L OLMEDA 26JUN95 CHK M ELLIS 26JUN95 APVD B BARE 26JUN95		AMP Incorporated Harrisburg, PA 17105-3608	
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±.015 3 PLC ±- 4 PLC ±- ANGLES ±-		NAME RECEPTACLE, 187 SERIES, FASTON™, PIDG™, WIRE SIZE, 26-24 AWG	
FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		VOLTAGE RATING: - -		MATERIAL BODY, BRASS .016 SLV, NYLON, COLOR, YELLOW		FINISH BODY, TIN -	
FOR ORDER ENTRY		1-800-526-5142		CIRCULAR MIL AREA: - -		CUSTOMER DRAWING		SCALE NT5 SHEET 1 OF 1 REV G	