735279 ✔ ACTIVE

FASTON

TE Internal #: 735279

Quick Disconnects, Receptacle, 22 – 18 AWG Wire Size, .26 – .96 mm² Wire Size, 509 – 1900 CMA Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight

View on TE.com >

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **509 – 1900 CMA**

Mating Tab Width: **6.35 mm [.25 in]**

Features

Product Type Features

Insertion Force	Normal

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire

Electrical Characteristics

Voltage Rating	300 V

Body Features

Insulation Material	Nylon

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	Compression

Barrel Type	Closed

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	21.5 mm[.846 in]
Compatible Insulation Diameter Range	3.3 mm[.13 in]
Wire Size	509 – 1900 CMA

Usage Conditions

Insulation Option	Fully Insulated
Operating Temperature Range	105 °C[221 °F]

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Other

Barrel Color	Red
Terminals & Splices Comment	Fully Insulated

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 47386
DAHT PG PIDG 26-16 ASSY



TE Part # 47386-4
DAHT PG PIDG 26-16 ASSY



TE Part # 539691-2
ERGO DIE R.B.Y



TE Part # 2063030-1
SDE DIESET, RBY, UL



TE Part # 169400
CERTI-LOK FRAME W/O DIES



TE Part # 169404
CERTI-LOK DIE

Customers Also Bought



TE Part #2-1630027-0
HSC300 6R8 5%



TE Part #1415076-1
PT5S7LC4



TE Part #5-867052-1
LOCKING CLIP CONT ASSY .025 SQ



TE Part #1-1609966-1
KES 3A 1S SPADE WYE 440VAC



TE Part #1-1609965-2

KEB 6A 1S SPADE DELTA 440VAC



TE Part #4-1622796-2

YR1 0.1% 97K6




TE Part #2234095-2

OCEAN-2.0-APPLICATOR-SA

TE Part #1-1659361-1

H31822/1000



TE Part #1-1102100-7

HA.3.STO.1.11

Documents

Product Drawings

REC FASTON SERIES 635 PIDG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_735279_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_735279_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_735279_L.3d_stp.zip

English

3D PDF

English

Customer View Model

ENG_CVM_735279_E.3d_igs.zip

English

Customer View Model

ENG_CVM_735279_E.3d_stp.zip

English

Customer View Model

ENG_CVM_735279_E.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

APPLICATION OF AMP FULLY INSULATED FASTON* RECEPTACLES (6,35mm)

English