




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Flag
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	13.72 mm[.54 in]
Compatible Insulation Diameter Range	2.79 – 4.06 mm[.11 – .16 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	11000
Packaging Method	Strip/Reel

Other

Line	Budget
Terminals & Splices Comment	Right handed flag.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free




Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



 TE Part # 62418-1 250 FASTON FLAG REC 22-16 AWG BR	 TE Part # 626089-1 250 FASTON FLAG REC 22-18 AWG BR	 TE Part # 1742999-3 250 FASTON,FLAG,REC.,18-14 AWG, TPBR	 TE Part # 1969899-1 250 FASTON HSG.,FLAG,REC.,2 POS, BLACK
 TE Part # 2-2150382-2 OCEAN_2.0_APPLICATOR-E-110F1800	 TE Part # 2150382-2 OCEAN_2.0_APPLICATOR-E-110F1800	 TE Part # 7-2150382-2 OCEAN_2.0_APPLICATOR-E-110F1800	 TE Part # 7-2150382-7 OCEAN_2.0_SPARE_PART_KIT-110F1800
 TE Part # 2150573-2 OC-AT-E-FA-110F1800-001-0059	 TE Part # 1-480306-1 250 FASTON INSULATION POD.,REC., NATURAL	 TE Part # 2-2150573-2 OC-PA-E-FA-110F1800-001-0059	

Also in the Series | FASTON 250



 Compression Connectors(4)	 Crimp Terminal Housings(142)	 Insertion & Extraction Tools(6)	 Magnet Wire Terminals(1)
 PCB Terminals(135)	 Quick Disconnects(445)	 Splices(4)	

Customers Also Bought

 TE Part #5-1971775-3 PTL 2X3 CAP PANEL MT HIGH TEMP KEY A LGR	 TE Part #1971785-1 PTL RECEPTACLE CONTACT, 20 - 24 AWG	 TE Part #794815-1 02P UMNL CAP HSG,HI TEMP	 TE Part #63963-1 250 FASTON FLAG REC 18-14 AWG NPST
 TE Part #62718-2 250 FASTON FLAG REC 22-18 AWG TPBR	 TE Part #42722-1 RING TONGUE 12-10 AWG BR	 TE Part #2238197-3 250 FASTON,FLAG,REC.,18-12 AWG, TPBR	 TE Part #1971788-2 PTL TAB CONTACT, 2X18 AWG
 TE Part #1217039-1 TIMER CONNECTOR GEN 3 18-14 POST-TPBR	 TE Part #353148-5 POSITIVE LOCK 187 HOUSING RECEPTACLE		

Documents



Product Drawings

250 FASTON FLAG REC 18-14 AWG TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63010-1_AF.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_63010-1_AF.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_63010-1_AF.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English

Agency Approvals

CSA Certificate

English

CSA Certificate

English