




Positive Lock | Positive Lock 187

TE Internal #: 175032-1

Quick Disconnects, Receptacle, 26 – 20 AWG Wire Size, .13 – .52 mm² Wire Size, Mating Tab Width 4.75 mm [.187 in], Straight, Positive Lock 187

[View on TE.com >](#)

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.13 – .52 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Stainless Steel
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------



Mechanical Attachment

Extraction Force	7 – 100 Newton
Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.3 mm[.012 in]
Product Length	17.2 mm[.68 in]
Compatible Insulation Diameter Range	1.3 – 3.6 mm[.051 – .141 in]
Wire Size	.13 – .52 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 250 °C[-40 – 482 °F]

Industry Standards

Agency/Standard	UL
-----------------	----

Packaging Features

Packaging Quantity	6000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 1-172210-1
187 HSG. PL MKII REC. 6mm 2P NAT

TE Part # 1743058-1
PL 187 REC 22-16 AWG 0.3 X 22.8 PTBR

TE Part # 2-2150047-2
OCEAN_2.0_Applicator-E-062F140F

TE Part # 2150047-2
OCEAN_2.0_Applicator-E-062F140F

TE Part # 7-2150047-2
OCEAN_2.0_Applicator-E-062F140F

TE Part # 7-2150047-7
OCEAN_2.0_SPARE_PART_KIT-062F140F

Also in the Series | Positive Lock 187


Crimp Terminal Housings(86)

Insertion & Extraction Tools(2)

Insulation Boots & Sleeves(7)

Quick Disconnects(55)

Customers Also Bought




TE Part #1376394-1
5MM POWER KEY D/L PLATE GREEN




TE Part #5-1478762-2
Metal backshell 15 way Top Entry-KIT



TE Part #5-147278-4
05 MTE HDR SRRA SFMNT .100CL




TE Part #173974-1
187 HSG. PL MKII REC. NAT



TE Part #170326-1
187 PL MKII REC. 18-14AWG PTBR



TE Part #1-967628-6
FLACHSTE-GEH2,8 15P



TE Part #1376350-2
025 I/O CAP HSG ASSY 8P



TE Part #1-962841-2
TAB 2.8x0.8 CONTACT CS SRC Ag



TE Part #3-968696-2
MQS STIFT-GEH 4P



TE Part #1742669-1
PL EX 187 REC 0.5-1.3MM2 NPST

Documents

Product Drawings

PL 187 REC 26-20 AWG 0.30 X 14.0 SS

Japanese

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_175032-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_175032-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_175032-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



Positive Lock Receptacles

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_175032-1_05032016236_dmtec

English

MD_175032-1_05032016236_dmtec

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

POSITIVE LOCK EX CONTACT

English