THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION – –, .
© COPYRIGHT – By – ALL RIGHTS RESERVED.

LOC	DIST
G	86

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	E2	REVISED PER ECO-11-005027	11MAR11	RK	HMR

AMP WIRE RANGE	FILE E66717	LR7189 Certified
12–10 AWG STRANDED	12–10 AWG STRANDED	12–10 AWG STRANDED

1. MARKED AMP 12-10
2. DESIGNED FOR WIRE INSULATION DIA OF .135-.210.
3. MATES WITH .250±.003 BY .032±.001 THK TAB.
4. BODY: BRASS, TIN PLATED SLEEVE: NYLON, YELLOW
5. RATED FOR 24 MAX AMPERE

QTY	PACKAGE TYPE	PART NO.
100	LOOSE PIECE	8-696371-1
1000	LOOSE PIECE	696371-1

TE CONNECTIVITY CUSTOMER SERVICE SYSTEM

FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWING AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1-800-722-1111
FOR ORDER ENTRY	1-800-526-5142

MAX RECOMMENDED OPERATING TEMPERATURE: 105°C [221°F] –

VOLTAGE RATING: 300V MAX –

CIRCULAR MIL AREA: 5,180-13,100 STRANDED

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± –
1 PLC	± –
2 PLC	± –
3 PLC	± .008
4 PLC	± –
ANGLES	± –

MATERIAL – 4

FINISH – 4

DWN	JR RUTH 07NOV01
CHK	T MICHIELUTTI 07NOV01
APVD	T MICHIELUTTI 07NOV01
PRODUCT SPEC	–
APPLICATION SPEC	114-13076
WEIGHT	–

TE Connectivity

NAME: RECEPTACLE, 250 SERIES, FASTON, FULLY INSULATED, WIRE: 12-10 AWG –

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-696371	–

CUSTOMER DRAWING | SCALE 1:1 | SHEET 1 OF 1 | REV E2

1470-19 (3/11)