




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.25 – .34 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

--	--



Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.08 mm[.003 in]
Product Length	16 mm[.63 in]
Compatible Insulation Diameter Range	1.02 – 1.52 mm[.04 – .06 in]
Wire Size	.25 – .34 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	10000
Packaging Method	Strip/Reel

Other

Line	Premier
------	---------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2-2150546-1
[OC-PA-E-FM-062F070O-001-0034](#)

TE Part # 2-2150546-2
[OC-PA-E-FA-062F070O-001-0034](#)

TE Part # 2150546-1
[OC-AT-E-FM-062F070O-001-0034](#)

TE Part # 2150546-2
[OC-AT-E-FA-062F070O-001-0034](#)

KIT
REPRESENTATION ONLY
TE Part # 7-2150546-7
[OC-062F070O-CRIMPTOOLINGKIT](#)

Also in the Series | FASTON 110

Crimp Terminal Housings(13)

Insertion & Extraction Tools(1)

PCB Terminals(21)


Quick Disconnects(172)

Customers Also Bought





TE Part #164163-1
PIN ASS



TE Part #281709-4
PLUG HE13 IDC 90 4 P AWG 24



TE Part #5-160490-2
187 FASTON REC 20-16 AWG TPBR




TE Part #350786-1
02P UMNL HDR ASSY 94VO



TE Part #1-2213766-7
AV19 SPM 5A POWER LED BLUE 12V



TE Part #5-1625885-1
1W SM M/OX 5% 27K



TE Part #1-216093-6
AMP-LATCH PRE-ASSY DIL WITHO



TE Part #9-1419111-4
PT571048

Documents

Product Drawings

110 FASTON,REC.,24-22 AWG,PTBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_140716-2_Z.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_140716-2_Z.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_140716-2_Z.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English



[Agency Approvals](#)
[Agency Approval Document](#)
English