




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **3.18 mm [.125 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	3.18 mm[.125 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.25 mm[.01 in]
Product Length	16.13 mm[.635 in]
Compatible Insulation Diameter Range	2.3 – 2.8 mm[.09 – .11 in]
Wire Size	.32 – .82 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	15000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



 TE Part # 1494217-1 110 FASTON,REC.,18-22 AWG,PB	 TE Part # 1494219-1 110 FASTON,REC.,18-22 AWG,BR	 TE Part # 2-2836604-1 OC-PA-E-FM-070F140O-001-0324	 TE Part # 2-2836604-2 OC-PA-E-FA-070F140O-001-0324
 TE Part # 2836604-1 OC-AT-E-FM-070F140O-001-0324	 TE Part # 2836604-2 OC-AT-E-FA-070F140O-001-0324	 TE Part # 7-2836604-7 OC-070F140O-CRIMPTOOLINGKIT	

Also in the Series | FASTON 125

Quick Disconnects(1)

Customers Also Bought



 <p>TE Part #179595-1 AMP POWER D/LOCK TAB CONT. L/P</p>	 <p>TE Part #6-1623746-9 ER74 R05 10% AMMO PK</p>	 <p>TE Part #53244-1 TERMINAL,PG SPR SPD 16-14 8</p>	 <p>TE Part #1-480699-9 02P UMNL CAP HSG BLK</p>
 <p>TE Part #179593-1 AMP POWER D/LOCK RECONT. L/P</p>	 <p>TE Part #1-480700-9 03P UMNL PLUG HSG BLK</p>	 <p>TE Part #1-480701-9 03P UMNL CAP HSG BLK</p>	 <p>TE Part #2-2213772-3 AV22 SPL 5A MOVE RING LED WHITE 24V</p>
 <p>TE Part #2-180930-5 250 FASTON HSG.,REC.,1 POS,BLACK</p>	 <p>TE Part #7-2176374-0 RQ 0805 562R 0.1% 10PPM 1K RL</p>		

Documents

Product Drawings

125 FASTON REC 22-18 AWG BR

English

CAD Files

Customer View Model

ENG_CVM_CVM_63705-1_G.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63705-1_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_63705-1_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English