



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.31 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	Without
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.3 mm[.012 in]
Product Length	12.06 mm[.475 in]
Wire Size	.51 – 1.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	24000
Packaging Method	Strip/Reel

Other

Terminals & Splices Comment	Economy Receptacle.
-----------------------------	---------------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 2-2150452-1 OCEAN_2.0_Applicator-E-090F	 TE Part # 2-2150452-2 OCEAN_2.0_Applicator-E-090FA	 TE Part # 2150452-1 OCEAN_2.0_Applicator-E-090F	 TE Part # 2150452-2 OCEAN_2.0_Applicator-E-090FA
 TE Part # 7-2150452-1 OCEAN_2.0_Applicator-E-090F	 TE Part # 7-2150452-2 OCEAN_2.0_Applicator-E-090FA	 TE Part # 7-2150452-7 OCEAN_2.0_SPARE_PART_KIT-090F	

Also in the Series | FASTON 187

 Crimp Terminal Housings(42)	 Insertion & Extraction Tools(1)	 Joints & Splices(1)	 PCB Terminals(42)
---------------------------------	-------------------------------------	-------------------------	-----------------------




Quick Disconnects(209)




Splices(1)


Customers Also Bought



TE Part #321253
TERMINAL,SOLIS FLAG R 2 3/8



TE Part #330021
SPLICE,CE 22-16



TE Part #42460-1
FF 250 TAB 18-14AWG BR



TE Part #62026-1
187 FASTON REC 20-16 AWG TPBR




TE Part #41711
RING TERMINAL 22-18 AWG TPBR




TE Part #63306-1
250 FASTON REC 18-14 AWG BR



TE Part #173724-1
187 PL EX REC. 20-14AWG PTBR



TE Part #1490749-1
HYP10 8-4/0AWG MANUAL TOOL



TE Part #1355556-1
MQS1,5 Sn rec LL unseal. 0,35-0,5



TE Part #1376477-4
2.5MM PITCH SIGNAL MATE CONN

Documents

Product Drawings

187 FASTON REC 20-16 AWG TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_61969-1_M.2d_dxf.zip

English

3D PDF



3D

Customer View Model

[ENG_CVM_CVM_61969-1_M.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_61969-1_M.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[82004 FASTON Terminals \(Insulated and Uninsulated\) Catalog - FASTON Receptacles Section](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[Product Compliance](#)

English

[Product Compliance](#)

English

Agency Approvals

[CSA Certificate](#)

English

[CSA Certificate](#)

English