TAI-SAW TECHNOLOGY CO., LTD.
No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.
TEL: 886-3-4690038 FAX: 886-3-4697532
E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Name: SAW Resonator 1GHz SMD 3.8X3.8 mm

TST Parts No.: TC0337A

Customer Parts No.:_____

Customer signature required

Company:_____

Division:_____

Approved by :_____

Date:_____

Checked by:_____ Hongpu Lin Hong Pu Lin

Approval by:_____ Andy Yu Andy Yu

Date:_____ 2019/08/05

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.

TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.
TEL: 886-3-4690038 FAX: 886-3-4697532
E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Resonator 1 GHz

MODEL NO.: TC0337A REV. NO.: 4.0

RoHS Compliant
Lead free
Lead-free soldering

A. FEATURES:

1. 1-Port Resonator.

B. MAXIMUM RATING:

1.Input Power Level: 10 dBm

2.DC voltage: 3 V

3.Operating Temperature: -40°C to +85°C

4.Storage Temperature: -40°C to +85°C


5.Moisture Sensitive Level: Level 1 (MSL1)

C. ELECTRICAL CHARACTERISTICS:


Characteristic	Units	Minimum	Typical	Maximum
Center frequency **Fr**	**MHz**	999.950	1000	1000.050
Insertion Loss **IL**	**dB**	-	1.75	2.3
Equivalent Elements				
Motional capacitance **C1**	**fF**	-	0.92	-
Motional inductance **L1**	**μH**	-	27.5	-
Motional resistance **R1**	**Ohm**	-	21.5	-
Parallel capacitance **Co**	**pF**	-	2.11	-
Temp.coeff.	**ppm/c*2**	-	0.032	-
Turnover To	**deg.C**	-	25	-
Package size		SMD 3.8X3.8X1.4mm		

D.EQUVIRENT CIRCUIT:

One-Port Resonator:



E.OUTLINE DRAWING:




△ Product Year Code

Year	2009 2013 2017	2010 2014 2018	2011 2015 2019	2012 2016 2020
Product Code	C	c	C	c


□ Date Code Table:

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z


F. FREUENCY CHARACTERISTICS



G. TEST CIRCUIT:




H. LAND PATTERN:




I. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION



J. RECOMMENDED REFLOW PROFILE:

