



NOTE FOR LEAD FREE CONVERSION:
 THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO ROHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.

- NOTES:
- 1) MATERIALS:
 INSULATOR IS GLASS FILLED LCP (LIQUID CRYSTAL POLYMER), U.L. 94 V-0, COLOR: BLACK; TERMINALS ARE A PHOSPHOR BRONZE ALLOY, .012" THICK.
 - 2) TERMINAL PLATING:
 30 MICROINCHES/(0.762 MICROMETERS) MINIMUM GOLD IN SELECTE AREA;
 100 MICROINCHES/(2.54 MICROMETERS) MINIMUM TIN IN SELECTE AREA;
 OVER NICKEL UNDERPLATE OVERALL.
 - 3) PARTS USED IN CONJUNCTION WITH MOLEX PRODUCT SPECIFICATION #PS-71719-9999.
 - 4) PACKAGING PER MOLEX SPECIFICATION #PK-70873-0252.
 - 5) PARTS CONFORM TO MOLEX APPLICATION SPECIFICATION #AS-71715-9999.

DIMENSIONS SHOWN <input type="checkbox"/> INCH <input checked="" type="checkbox"/> METRIC		▽ = 0 ▼ = 0 REVISE ONLY ON CAD SYSTEM	
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°		TITLE .050" PITCH LFH, 50 CKT. MALE INSERT-MOLDED CONTACT STRIP, SALES DETAIL	
3 PLACE ± .010 ---		SHEET NO. DATE 1 OF 1 04/23/96	
2 PLACE ± --- ± ---		MOLEX INCORPORATED U.S.A.	
1 PLACE --- ± ---		PART NO. 71715-4001 DRWG. NO. SDA-71715-4001	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		FILE NAME 57171504 DGN	
DRWG. BY GLT	CHK'D. BY GLT	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
APP'D. BY CWF	SCALE 5 : 1	DIV. SIZE CPP C	
LTR. REVISIONS	LTR. REVISIONS		