



- NOTES: (c) (d) (e)
- HOOD: PBT GF UL 94 V0, BLACK
TEMPERATURE RANGE -30°C TO +90°C
 - PG-GLAND: PA UL 94 V0
TEMPERATURE RANGE -30°C TO +90°C
 - FRONTSEALING: TPE UL 94 V0
TEMPERATURE RANGE -30°C TO +90°C
 - O-RING FOR PG-GLAND: NBR
TEMPERATURE RANGE -30°C TO +90°C
 - JACK SCREWS: STAINLESS STEEL
RECOMMENDED TORQUE: 30Ncm
 - WASHER: STAINLESS STEEL
 - O-RING FOR JACK SCREWS: NBR
TEMPERATURE RANGE -30°C TO +90°C

Shell-size	A	B	C	φD	E	F	G ^{±1}	H	RECOMMENDED TORQUE FOR PG-GLAND	Cable φ	Part NO.
1	40.76	25.0	SW 22	24.6	51.0	22.0	77.0	44.0	3.0 Nm	5 - 10	165X14-819X
2	49.06	33.3	SW 24	26.5	51.0	22.0	79.0	52.0	4.5 Nm	6 - 12	165X14-829X
3	62.80	47.04	SW 24	26.5	59.5	22.0	87.5	52.0	4.5 Nm	6 - 12	165X14-839X
4	78.86	63.5	SW 33	36.2	67.0	22.0	99.0	52.0	4.0 Nm	9 - 16	165X14-849X
5	76.46	61.1	SW 42	47.0	67.0	24.8	107.0	52.0	6.0 Nm	13 - 20	165X14-859X

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm	
	2002	date	name	
	drawn	13.02.	Parei	
	appd.	13.02.	E.Mickenbecker	
	2 x e	Ä4303	08.05.2012	K.H.
3 x d	Ä3678	24.06.2010	Petker	norm
1 x c	Ä3141	13.10.2008	Sonne	d-old
2 x b	Ä1741	26.02.2003	Parei	
a	Original			
rev.	description	date	name	

scale: 1:1
material: SEE NOTES

title: WATER RESISTANT D-SUB HOOD
9-50pos.
with jack screw 4-4.0 UNC

dwg no: 16K1A489

part no: SEE TABLE

DIN-A 3 sh: 1/1



Directive 2002/95/EC RoHS compliant