



NOTES:
 MATERIAL:
 HOOD: POLYAMID 6.6 GF 25 UL 94 V-0; BLACK
 SCREW: COPPER ALLOY; NICKEL PLATED
 CLAMP: STEEL; NICKEL PLATED

NO. OF POS.	A	B	C	D	PART NO.
9	31.2	25.0	22.8	8.0	165X13179X
25	53.5	47.0	44.8	10.3	165X13199X
37	69.7	63.5	61.3	10.3	165X13209X

used for: D-SUB

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND



1994	date	name	1994	date	name
drawn	23.03.	Barcinski	drawn	23.03.	Barcinski
appd.	23.03.	Mickenbecker	appd.	23.03.	Mickenbecker
norm		DIN 41652	norm		DIN 41652
d-old		16V1100A	d-old		16V1100A

tolerance	±0.3		scale:	2:1	
material:			material:	SEE NOTES	
title:			title:	TWO-PART HOOD	
				9, 25 and 37pos. FOR CABLE BINDING	
				FLAT VERSION	
dwg no:	AutoCADREL.13 DIN-A		dwg no:	16V1100B	
				3	
				sh: 1/1	
part no:	SEE TABLE		part no:	SEE TABLE	