



(b)

| Shellsize | A | B | C | φD | E | F | G ⁺¹ ₋₃ | Cable φ | Part-No. Bulk package | Part-No. Single package |
|-----------|-------|-------|-------|------|------|------|-------------------------------|---------|--------------------------|----------------------------|
| 1 | 40.76 | 25.0 | SW 22 | 24.6 | 51.0 | 22.0 | 77.0 | 5 - 10 | 165X14869X | 165X14869XE |
| 2 | 49.06 | 33.3 | SW 24 | 26.5 | 51.0 | 22.0 | 79.0 | 6 - 12 | 165X14879X | 165X14879XE |
| 3 | 62.80 | 47.04 | SW 24 | 26.5 | 59.5 | 22.0 | 87.5 | 6 - 12 | 165X14889X | 165X14889XE |
| 4 | 78.86 | 63.5 | SW 33 | 36.2 | 67.0 | 22.0 | 99.0 | 9 - 16 | 165X14899X | 165X14899XE |
| 5 | 76.46 | 61.1 | SW 42 | 47.0 | 67.0 | 24.8 | 107.0 | 13 - 20 | 165X14909X | 165X14909XE |

NOTES:
1. HOOD: PBT GF; BLACK
2. SCREWS: STAINLESS STEEL

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND

| | | | | | |
|---------------------|-------------|---|--------|---------------------------|--|
| tolerance | | dim. in mm | | scale: 1:1 | |
| material: SEE NOTES | | title: WATER RESISTANT D-SUB HOOD 9-50pos. with short screw | | dwg no: 16K1A1289 | |
| 2004 date | | name | | DIN-A 3 | |
| drawn 25.11. | | Lehmenkühler | | sh:1/1 | |
| appd. 25.11. | | Mickenbecker | | part no: SEE TABLE | |
| norm | | | | | |
| d-old | | | | | |
| 1 x b | Ä 4085 | 31.08.2011 | Lehmen | CONEC [®] | |
| a | Original | | | | |
| rev. | description | date | name | | |

