




This drawing is the property of Tusonix, Inc., and may not be used, reproduced, published or disclosed to others without expressed authorization by Tusonix Inc.

**MARKETING SALES DRAWING**  
**DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING**  
**DIMENSIONS IN METRIC - [ ]**



**Electrical Testing**  
**per Tusonix standard**  
**test plans and Mil-Std-202**  
**Test Methods.**



**SPECIFICATIONS**

TUSONIX STYLE.	2499-003
Capacitance Value:	1000 pF
Capacitance Tolerance:	-0% +100%
Temp. Characteristics:	X7R
Rating:	250 WVDC @ 125 °C
Current (A):	20
IR Min @ 100 vdc	10 GΩ
DWV	1500 VDC
Operating Range:	-55° TO + 125°C

**NOTES:**

- SUPPLIED WITH SILVER PLATED HEX NUT AND INTERNAL TOOTH LOCK WASHER.
- TUSONIX STANDARD PART  
 NUMBER: 2499-003-X7R0-102P.  
 TUSONIX R.o.H.S. COMPLIANT PART  
 NUMBER: 2499-003-X7R0-102P LF.  
 CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
- PART MARKING: TRADEMARK, CAPACITANCE CODE AND TOLERANCE CODE STAMPED ON BUSHING HEX FLATS:  
 STANDARD PART: BLACK MARKING.  
 RoHS COMPLIANT PART: GREEN MARKING.

X-2015 Rev-0

REVISION RECORD Original Release <b>ECO-2602</b>	<b>A</b>	<b>--TOLERANCES--</b> Unless Otherwise Specified	Title <b>BUSHING TYPE FEED-THRU CAPACITOR</b>	
		ANGLES ±	Drawn L.E. 01-17-12	Scale 3X
		<b>TUSONIX</b> TUCSON, ARIZONA	Approved R.L. 01-17-12	<b>A</b> 2499-003-X7R0-102P