




# MARKETING SALES DRAWING

**DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING**  
**DIMENSIONS IN METRIC - [ ]**

This drawing is the property of Tusonix, Inc., and may not be used, reproduced, published or disclosed to others without expressed authorization by Tusonix Inc.

**Electrical Testing**  
**per Tusonix standard**  
**test plans and Mil-Std-202**  
**Test Methods.**



## SPECIFICATIONS

TUSONIX STYLE.	2499-003
Capacitance Value:	1500 pF
Capacitance Tolerance:	+20%
Temp. Characteristics:	X5S
Rating:	500 WVDC @ 85°C
Current (A):	20
IR Min @ 100 vdc	10 GΩ
DWV	1500 VDC
Operating Range:	-55° TO + 85°C

## NOTES:

- SUPPLIED WITH SILVER PLATED HEX NUT AND INTERNAL TOOTH LOCK WASHER.
- TUSONIX STANDARD PART  
 NUMBER: 2499-003-X5S0-152M.  
 TUSONIX R.o.H.S. COMPLIANT PART  
 NUMBER: 2499-003-X5S0-152M LF.  
 CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
- PART MARKING: TRADEMARK, CAPACITANCE CODE AND TOLERANCE CODE STAMPED ON BUSHING HEX FLATS:  
 STANDARD PART: BLACK MARKING.  
 RoHS COMPLIANT PART: GREEN MARKING.

X-2015 Rev-0

REVISION RECORD	Original Release C.O. 19980605-5-01	0	<b>TUSONIX</b> TUCSON, ARIZONA	--TOLERANCES-- Unless Otherwise Specified	Title <b>BUSHING TYPE FEED-THRU CAPACITOR</b>	
	DIM'S IN METRIC & NOTE ADDED, SPEC. TABLE REVISED L.E. 01-27-04	1		DECIMAL ± .015 [0.38]	Drawn S.M. 06-05-98	Scale 3x
	ADDED NOTES 2 & 3. DIM 051 METRIC WAS 1.29. S.M. 07-24-06	2		ANGLES ±	Approved J.Mc. 06-05-98	
	REDRAWN BUSHING WITH SHOULDER. S.M. 08-09-06	3			A 2499-003-X5S0-152M	