

SC

**MULTIMODE SIMPLEX
ADAPTOR**

ZIRCONIA ALIGNEMENT SLEEVE


Packaging :
1

F 7 2 8 7 0 0 7 0 0

Packaging :
100

F 7 2 8 7 1 0 7 0 0

Original dimensions in mm [inch]



GENERAL

Type : IEC 61754-4 SC type. Push-pull latching system
Body color : beige

Mounting : flange screw - in mounting

Alignment sleeve : zirconia

CHARACTERISTICS (Dependant on fiber or cable construction)

Material : **Plastic moulded** Material in accordance with BELLCORE GR 326 CORE Issue 2, par. 3.3.1 Inflammability V1 (UL94)

Optic : Attenuation (according to IEC 1300-3-4:Substitution method, 7 type) at 1310nm : < 0,1 dB

Mechanical : **Durability** Bellcore 326, 200 cycles
Plug Retention > 68N

Environmental : **Temperature range** (storage/operating) -40°C to +85°C / -40°C to +70°C

Salt spray : EIA/TIA-455-16A, 35°C, 168 hr.

Vibration test : Bellcore 326, 10 to 50 Hz, 2 hrs./axis

Proof test : Bellcore 326, Straight pull : 6,8Kg load at 0°
Side pull : 3,5 Kg load at 90°

CREATION

N° :				
PEN/EP : CAT.				
Name : CAUSSE C.				
Date : 23.Jul.99				
App. :	Issue	Revisions	Name	App.

RADIALL

101, rue P. Hoffmann - Z.I. Ouest
93116 ROSNY / BOIS Cedex-France
Phone : (0033) 149353535
Fax : (0033) 48546363