



- Notes:**
- Material and Finish:
    - Coupler Ring: Polyester (Black); UL94 V-0
    - Plug Housing: Polyester (Black); UL94 V-0
    - Cable Gland: PA (Black), UL94 V-0
    - Cable Gland Rubber Ring: NBR, Color: Black
    - Cable Fitting: PA (Black), UL94 V-0
    - Interfacial Seal: Silicon, Color: White
    - Protective Cap: Polyester (Black); UL94 V-0
    - Tether: Polycarbonate (Black)
  - Duplex LC Connector
    - Housing: PEI, UL94 V-0, Color: **SM Blue/MM Beige/APC SM Green**
    - Inner Sub Assembly: Zirconia, Metal and PTFE
    - Crimp Barrel: Brass, Nickel Plated
    - Ferrule: Brass, Nickel Plated
    - Dust Cap: PC, Color: White
    - Duplex LC Clip: PC, Color: Black
    - Operating Temperature: -40~C to +85~C
  - IP67 rated when covered or fully mated with the appropriate mating connector
  - Accept 4.5mm to 8.0mm outside diameter fiber optic cable

Directive 2002/95/EC RoHS Compliant

Description	Part Number
Plastic Duplex LC Single Mode Plug Kit + Plug Cover Assembly	17-300200
Plastic Duplex LC Multi Mode Plug Kit + Plug Cover Assembly	17-300210
Plastic Duplex LC APC Single Mode Plug Kit + Plug Cover Assembly	17-300220

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.	Customer:			Tolerance Unless otherwise specified 0 PLC ±0.30 1 PLC ±0.20 2 PLC ±0.10 3 PLC ±0.05 ANGLES ±1°		Scale: NTS	Dim. in mm
	Name	Title	Approval Date			Material: See Notes	
				2011	Date	Name	Title: IP67 Industrial Duplex LC Plug + Protective Cover Assembly Kit Plastic Version
				Draw.	Mar. 04	Vincent Ke	
				Appd.	Mar. 04	J. Chaudry	
				Norm		Drawing No.: 17K1A216	
				D-old			
b	original	Jul/12/2011	Vincent ke			Part No.: SEE P/N ABOVE	DIN A3
a	Changes	Date	Name				Sheet 1/1