


T-43-15 14

54/7414
54LS/74LS14
 HEX SCHMITT TRIGGER INVERTER

CONNECTION DIAGRAM
 PINOUT A



ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0 \text{ V} \pm 5\%$, $T_A = 0^\circ\text{C to } +70^\circ\text{C}$	$V_{CC} = +5.0 \text{ V} \pm 10\%$, $T_A = -55^\circ\text{C to } +125^\circ\text{C}$	
Plastic DIP (P)	A	7414PC, 74LS14PC		9A
Ceramic DIP (D)	A	7414DC, 74LS14DC	5414DM, 54LS14DM	6A
Flatpak (F)	A	7414FC, 74LS14FC	5414FM, 54LS14FM	3I

INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.)	54/74LS (U.L.)
	HIGH/LOW	HIGH/LOW
Inputs	1.0/1.0	0.5/0.25
Outputs	20/10	10/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3*

SYMBOL	PARAMETER	54/74		54/74LS		UNITS	CONDITIONS
		Min	Max	Min	Max		
V_{T+}	Positive-going Threshold Voltage	1.5	2.0	1.5	2.0	V	$V_{CC} = +5.0 \text{ V}$
V_{T-}	Negative-going Threshold Voltage	0.6	1.1	0.6	1.1	V	$V_{CC} = +5.0 \text{ V}$
$V_{T+} - V_{T-}$	Hysteresis Voltage	0.4		0.4		V	$V_{CC} = +5.0 \text{ V}$
I_{T+}	Input Current at Positive-going Threshold	-0.43**		-0.14**		mA	$V_{CC} = +5.0 \text{ V}, V_{IN} = V_{T+}$
I_{T-}	Input Current at Negative-going Threshold	-0.56**		-0.18**		mA	$V_{CC} = +5.0 \text{ V}, V_{IN} = V_{T-}$
I_{iL}	Input LOW Current	-1.2		-0.4		mA	$V_{CC} = \text{Max}, V_{IN} = 0.4 \text{ V}$
I_{oS}	Output Short Circuit Current	-18 -55		-20 -100		mA	$V_{CC} = \text{Max}, V_{OUT} = 0 \text{ V}$
I_{CCH}	Power Supply Current	36		16		mA	$V_{IN} = \text{Gnd}$
I_{CCL}		60		21			$V_{IN} = \text{Open}$
t_{PLH} t_{PHL}	Propagation Delay	22		22		ns	Figs. 3-1, 3-15

*DC limits apply over operating temperature range; AC limits apply at $T_A = +25^\circ\text{C}$ and $V_{CC} = +5.0 \text{ V}$. **Typical Value