

Uni-Dicht-Verschraubung Pg13,5 6,5-9,5mm



Specification	Uni-Dicht-Verschraubung Pg13,5 6,5-9,5mm
HARTING eCatalogue	https://b2b.harting.com/0900005083

09 00 000 5083

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Accessories
Type of accessory	Cable gland

Part number

Technical characteristics

Tightening torque	≤10 Nm (depending on the cable and the seal insert used)
Wrench size	22
Limiting temperature	-40 +130 °C
Degree of protection acc. to IEC 60529	IP68
Size	Pg 13.5
Clamping range	6.5 9.5 mm

Material properties

Material (cable glands)	Metal
Colour (accessories)	Black
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes

Page 1 / 2 | Creation date 2022-11-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

	Lead
California Proposition 65 substances	Nickel
	Naphthalene

Commercial data

Packaging size	10
Net weight	32.4 g
Country of origin	Germany
European customs tariff number	84849000
GTIN	5713140001640
eCl@ss	27140801 Screwed cable gland (electrical)