

Pneum. contact metal OD 3 female



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 14 000 6453 |
| Specification | Pneum. contact metal OD 3 female |
| HARTING eCatalogue | https://b2b.harting.com/09140006453 |

Identification

| | |
|----------------------------|--|
| Category | Contacts |
| Type of contact | Pneumatic contact |
| Description of the contact | Without shut-off Straight |
| Features | The Han® Pneumatic contacts without shut-off are suitable for the use inside a vacuum. (Limit: 100 mbar = 100 hPa ≈ approx 90% vacuum) |

Version

| | |
|-----------------------|-----------------|
| Gender | Female |
| Manufacturing process | Turned contacts |

Technical characteristics

| | |
|----------------------|------------------------------------|
| Limiting temperature | -20 ... +85 °C Tube outer diameter |
| Operating pressure | ≤10 bar |
| Tube outer diameter | 3 mm |

Material properties

| | |
|-----------------------------|--|
| Material (contacts) | Brass |
| Material (seal) | NBR |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|--------------------------------------|
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | b51e5b97-eeb5-438b-8538-f1771d43c17d |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |

Specifications and approvals

| | |
|----------|--|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
|----------|--|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 10 |
| Net weight | 12 g |
| Country of origin | Germany |
| European customs tariff number | 39269097 |
| GTIN | 5713140189119 |
| eCl@ss | 27440204 Contact for industrial connectors |