

## Han 300A module short, female



Image is for illustration purposes only. Please refer to product description.

Part number	09 14 001 3105
Specification	Han 300A module short, female
HARTING eCatalogue	<a href="https://b2b.harting.com/09140013105">https://b2b.harting.com/09140013105</a>

### Identification

Category	Modules
Series	Han-Modular®
Type of module	Han® 300 A module, for busbar
Size of the module	Double module

### Version

Termination method	Screw termination
Gender	Female
Number of contacts	1
Details	Please order contacts separately.

### Technical characteristics

Rated current	300 A
Rated voltage	1,000 V
Rated voltage	1,000 V AC 1,300 V DC
Rated impulse voltage	8 kV
Pollution degree	3
Insulation resistance	$>10^{10} \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	$\geq 500$



Pushing Performance  
Since 1945

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Specifications	EN 50124-1 IEC 60664-1 IEC 61984
----------------	--

## Commercial data

Packaging size	1
Net weight	19 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140184480
eCl@ss	27440217 Module for industrial connectors (power/signals)